

Nabco Entrances - Bi-part Slide Door Shop Drawing Request

Page: _____ of _____
 Company: _____ Distributor #: _____ Door #: _____
 Date: _____ Job Name: _____
 _____ Contact: _____

Notes:

Type of Unit: Bi-part

GT1175 - drawing # _____

Jamb Tubes: _____ None Required

_____ Quantity
 _____ Standard _____ Fixed Sidelite
 _____ Hurricane _____ Full Open
 _____ All-Glass _____ Pocketed
 _____ _____ Surface applied (see note 1)
 _____ _____ to interior
 _____ _____ to exterior
 _____ _____ with sidelite
 _____ _____ no sidelite

_____ Standard
 _____ 1-3/4" x 4-1/2" Single Pocket
 _____ 1-3/4" x 4-1/2" Double Pocket
 _____ 1-3/4" x 4-1/2" Without Pockets
 _____ 1-3/4" x 6-3/8"
 _____ 2" x 5"
 _____ 2" x 7"
 _____ 4-1/2" x 4-1/2" Jamb Tubes
 _____ (except All Glass or Telescopic)

Frame Size:

Muntin Bars:

_____ Width
 _____ Header Height (std. = 91-1/2")
 _____ Height Including Transom
 _____ Number of Verticals in Transom
 _____ Clear Door Opening Width

_____ 2" std.
 _____ 4"
 _____ 6-3/8"
 _____ No muntins required
 _____ Special _____
 _____ Standard Height 42-1/4" F.F. - top
 _____ Special location - F.F. - top
 _____ Additional Muntin - F.F. - top
 _____ 6-3/8" Muntin Std. - Recessed Panic

Door/Panel Glass Thickness

Transom Glass Thickness

_____ 1/4" (std.)	_____ 1/4" (std.)
_____ 1/2"	_____ 1/2"
_____ 9/16"	_____ 9/16"
_____ 5/8"	_____ 5/8"
_____ 3/4"	_____ 3/4"
_____ 7/8"	_____ 7/8"
_____ 1"	_____ 1"
_____ Hurricane	

Additions/Changes:

Finish:

_____ Optex x-Zone (in lieu of Acusensor)
 _____ Acuvision (in lieu of Acusensor)
 _____ Optex i-One (in lieu of Acusensor)
 _____ BEA Wizard (in lieu of Acusensor)
 _____ Medium Stile (4")
 _____ Fail Safe Electric Lock
 _____ Fail Secure Electric Lock
 _____ Fail Safe Electro-Magnetic Lock
 _____ Surface applied push bar exit hardware
 _____ Recessed push bar exit hardware
 _____ Paddle exit hardware (Fixed Sidelite)
 _____ Key Switches in lieu of Rocker Switch
 _____ Qty of additional Holding Beams
 _____ Reposition access cover to
 _____ opposite side of header.
 _____ Rail Locks for All Glass Sliders
 _____ Include Weathering for All Glass
 _____ Prep as Clean Room unit
 _____ (except Telescopic or All Glass)
 _____ Rocker switches on interior jamb face
 _____ _____ Specify LT or RT side.
 _____ Aluminum Cart Bars P/N 14-11035
 _____ (except All Glass)
 _____ (specify which panels to receive bars)
 _____ Key cylinder operated flush bolts
 _____ (Hurricane unit only)

_____ Clear (204)
 _____ Dk bronze (313)
 _____ Special anodize _____
 _____ Paint/Clad _____
 _____ Prep for paint by distributor

Threshold:

_____ Through Door Opening _____ Under Jambs
 _____ Between Jambs _____ Other

Bottom Rail:

_____ Standard _____ 10"
 _____ Other _____

Note 1

On surface applied units, indicate the desired location of rocker switches in Notes area at bottom right.

Restrictions:

On hurricane rated sliders not all options are applicable
Refer to worksheets for certain restrictions