

# Nabco Entrances - Single Slide - Shop Drawing Request

Page: \_\_\_\_\_ of \_\_\_\_\_  
 Company: \_\_\_\_\_ Distributor #: \_\_\_\_\_ Door #: \_\_\_\_\_  
 Date: \_\_\_\_\_ Job Name: \_\_\_\_\_  
 \_\_\_\_\_ Contact: \_\_\_\_\_

Notes:

**Type of Unit:** GT1175 - drawing # \_\_\_\_\_  
 \_\_\_\_\_ Quantity  
 \_\_\_\_\_ Bi-part \_\_\_\_\_ Fixed Sidelite  
 \_\_\_\_\_ Single \_\_\_\_\_ Full Open  
 \_\_\_\_\_ \_\_\_\_\_ Pocketed  
 \_\_\_\_\_ Telescopic \_\_\_\_\_ Surface applied (\* see note 1)  
 \_\_\_\_\_ All-Glass \_\_\_\_\_ to interior  
 \_\_\_\_\_ Hurricane \_\_\_\_\_ to exterior  
 \_\_\_\_\_ \_\_\_\_\_ with sidelite  
 \_\_\_\_\_ \_\_\_\_\_ no sidelite

**Hand of Unit:**  
 \_\_\_\_\_ Right hand *viewed from exterior*  
 \_\_\_\_\_ Left hand *panic breakaway direction*

**Frame Size:**  
 \_\_\_\_\_ Width  
 \_\_\_\_\_ Header Height (std. = 91-1/2")  
 \_\_\_\_\_ Height Including Transom  
 \_\_\_\_\_ Number of Verticals in Transom  
 \_\_\_\_\_ Clear Door Opening Width

Door/Panel Glass Thickness	Transom Glass Thickness
_____ 1/4" (std.)	_____ 1/4" (std.)
_____ 1/2"	_____ 1/2"
_____ 9/16"	_____ 9/16"
_____ 5/8"	_____ 5/8"
_____ 3/4"	_____ 3/4"
_____ 7/8"	_____ 7/8"
_____ 1"	_____ 1"
_____ Hurricane	

**Finish:**  
 \_\_\_\_\_ Clear (204)  
 \_\_\_\_\_ Dk bronze (313)  
 \_\_\_\_\_ Special anodize \_\_\_\_\_  
 \_\_\_\_\_ Paint/Clad \_\_\_\_\_  
 \_\_\_\_\_ Prep for paint by distributor

**Threshold:**  
 \_\_\_\_\_ Through Door Opening \_\_\_\_\_ Under Jambs  
 \_\_\_\_\_ Between Jambs \_\_\_\_\_ Other

**Note 1:** On surface applied units, indicate the desired location of rocker switches in Notes area at bottom right of this form.

**Restrictions:**  
On hurricane rated sliders not all options are applicable  
Refer to worksheets for certain restrictions

**Jamb Tubes:** \_\_\_\_\_ None Required  
 \_\_\_\_\_ Standard  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Single Pocket  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Double Pocket  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Without Pockets  
 \_\_\_\_\_ 1-3/4" x 6-3/8"  
 \_\_\_\_\_ 2" x 5"  
 \_\_\_\_\_ 2" x 7"  
 \_\_\_\_\_ 4-1/2" x 4-1/2" Jamb Tubes  
 (except All Glass or Telescopic)

**Muntin Bars:**  
 \_\_\_\_\_ 2" std.  
 \_\_\_\_\_ 4" \_\_\_\_\_ 6-3/8"  
 \_\_\_\_\_ 8"  
 \_\_\_\_\_ No muntins required  
 \_\_\_\_\_ Special \_\_\_\_\_  
 \_\_\_\_\_ Standard Height 42-1/4" F.F. - top  
 \_\_\_\_\_ Special location - F.F. - top  
 \_\_\_\_\_ Additional Muntin - F.F. - top  
 \_\_\_\_\_ 6-3/8" Muntin Std. - Recessed Panic

**Bottom Rail:**  
 \_\_\_\_\_ Standard \_\_\_\_\_ 10"  
 \_\_\_\_\_ Other \_\_\_\_\_

**Additions/Changes:**  
 \_\_\_\_\_ Optex x-Zone (in lieu of Acusensor)  
 \_\_\_\_\_ Acuvision (in lieu of Acusensor)  
 \_\_\_\_\_ Optex i-One (in lieu of Acusensor)  
 \_\_\_\_\_ BEA Wizard (in lieu of Acusensor)  
 \_\_\_\_\_ Medium Stile (4")  
 \_\_\_\_\_ Fail Safe Electric Lock  
 \_\_\_\_\_ Fail Secure Electric Lock  
 \_\_\_\_\_ Fail Safe Electro-Magnetic Lock  
 \_\_\_\_\_ Surface applied push bar exit hardware  
 \_\_\_\_\_ Recessed push bar exit hardware  
 \_\_\_\_\_ Paddle exit hardware (Fixed Sidelite)  
 \_\_\_\_\_ Key Switches in lieu of Rocker Switch  
 \_\_\_\_\_ Qty. of Additional Holding Beams  
 \_\_\_\_\_ Reposition access cover to  
 \_\_\_\_\_ opposite side of header.  
 \_\_\_\_\_ Rail Locks for All Glass Sliders  
 \_\_\_\_\_ Include Weathering for All Glass  
 \_\_\_\_\_ Prep as Clean Room unit

\_\_\_\_\_ Rocker switches on interior jamb face  
 \_\_\_\_\_ Specify LT or RT side.  
 \_\_\_\_\_ Aluminum Cart Bars P/N 14-11035  
 (specify which panels to receive bars)  
 \_\_\_\_\_ Key cylinder operated flush bolts  
 (Hurricane unit only)