# Nabco Entrances-Telescopic Slide Door Shop Drawing Request

Page: _____ of _____

Company: _____ Distributor #: _____ Door #: _____

Date: _____ Job Name: _____

_____ Contact: _____

Notes:

**Type of Unit:** GT1175 - drawing # _____

_____ Quantity

_____ Bi-part _____ Fixed Sidelite

_____ Single _____ Full Open

_____ Surface applied **(* see note 1)**

_____ to interior

_____ to exterior

_____ with sidelite

_____ no sidelite

**Hand of Unit:**

_____ Right hand *view from exterior*

_____ Left hand *panic breakaway direction*

**Frame Size:**

_____ Width

_____ Header Height (std. = 91-1/2")

_____ Height Including Transom

_____ Number of Verticals in Transom

_____ Clear Door Opening Width

**Door/Panel Glass Thickness**

_____ 1/4" (std.)

_____ 1/2"

_____ 9/16"

_____ 5/8"

_____ 3/4"

_____ 7/8"

_____ 1"

**Transom Glass Thickness**

_____ 1/4" (std.)

_____ 1/2"

_____ 9/16"

_____ 5/8"

_____ 3/4"

_____ 7/8"

_____ 1"

**Finish:**

_____ Clear (204)

_____ Dk bronze (313)

_____ Special anodize

_____ Paint/Clad

_____ Prep for paint by distributor

**Threshold: (see note 2)**

_____ Through Door Opening

_____ Between Jambs

_____ Under Jambs

_____ Other

**Jamb Tubes:**

_____ Standard (2" x 7")

_____ No Jambs Required

**Muntin Bars:**

_____ 2" std. _____ 6-3/8"

_____ 4"

_____ No muntins required

_____ Special _____

_____ Standard Height 42-1/4" F.F. - top

_____ Special location - F.F. - top

_____ Additional Muntin - F.F. - top

_____ 6-3/8" Muntin Std. - Recessed Panic

**Bottom Rail:**

_____ Standard _____ 10"

_____ Other _____

**Additions:**

_____ Acuvision (in lieu of Acusensor)

_____ Optex i-One (in lieu of Acusensor)

_____ Optex X-Zone (in lieu of Acusensor)

_____ BEA Wizard (in lieu of Acusensor)

_____ Medium Stile (4")

_____ Fail Safe Electric Lock

_____ Fail Secure Electric Lock

_____ Fail Safe Electro-Magnetic Lock

_____ Surface applied push bar exit hardware

_____ Recessed push bar exit hardware

_____ Paddle exit hardware (Fixed Sidelite)

_____ Key Switches in lieu of Rocker Switch

_____ Qty of additional Holding Beams

_____ Rocker switches on interior jamb face

_____ Specify LT or RT side.

**Note 2:** Threshold jamb to jamb is necessary on a full open unit. Any threshold option is available for fixed units.

**Note 1:**

Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limied to one side of the header. We rip the hook off the cover on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on. If you