Nabco Entrances - Bi-part Slide - ORDER FORM Rev 5-13B Order Page: Company: ___ Distributor #: _____ Door #: _____ Date: Job Name: PO #: Contact: Drop Ship to: Ship Method: Date to Ship: Notes: Type of Unit: Bi-part GT1175 - drawing # Jamb Tubes: None Required Standard Quantity 1-3/4" x 4-1/2" Single Pocket Fixed Sidelite Standard 1-3/4" x 4-1/2" Double Pocket Full Open 1-3/4" x 4-1/2" Without Pockets Hurricane Pocketed All-Glass 1-3/4" x 6-3/8" Surface applied (see note 1) 2" x 5" to interior 2" x 7" to exterior 4-1/2" x 4-1/2" Jamb Tubes Frame Size: with sidelite (except All Glass or Telescopic) no sidelite Width Header Height (std. = 91-1/2") **Muntin Bars:** Height Including Transom 2" std. Number of Verticals in Transom 4" Clear Door Opening Width 4-1/2" 6-3/8" **Transom Glass Thickness Door/Panel Glass Thickness** No muntins required Special 1/4" (std.) 1/4" (std.) 1/2" 1/2" Standard Height 42-1/4" F.F. - top . 9/16" . 9/16" Special location - F.F. - top 5/8" 5/8" Additional Muntin - F.F. - top

3/4"	3/4"	6-3/8" Muntin Std Recessed Panic
7/8"	7/8"	
1"	1"	Additions/Changes:
Hurricane		Optex x-Zone (in lieu of Acusensor)
		Acuvision (in lieu of Acusensor)
Finish:		Optex i-One (in lieu of Acusensor)
Clear (204)		BEA Wizard (in lieu of Acusensor)
Dk bronze (313)		Medium Stile (4")
Special anodize		Fail Safe Electric Lock
Paint/Clad		Fail Secure Electric Lock
Prep for paint by distributor		Fail Safe Electro-Magnetic Lock
		Surface applied push bar exit hardware
Threshold:		Recessed push bar exit hardware
Through Door Opening	Under Jambs	Paddle exit hardware (Fixed Sidelite)
Between Jambs	Other	Key Switches in lieu of Rocker Switch
		Qty of additional Holding Beams
Bottom Rail:		Reposition access cover to
Standard 1	0"	opposite side of header.
Other		Rail Locks for All Glass Sliders
Note 1		Include Weathering for All Glass
On surface applied units, indicate the des	sired location of	Prep as Clean Room unit
rocker switches in Notes area at bottom r	ight.	(except Telescopic or All Glass)
		Rocker switches on interior jamb face
Restrictions:		Specify LT or RT side.
On hurricane rated sliders not all options are applicable		Aluminum Cart Bars P/N 14-11035
Refer to worksheets for certain restriction	<u>ıs</u>	(except All Glass)
		(specify which panels to receive bars)

Key cylinder operated flush bolts

(Hurricane unit only)