

Nabco Entrances - Bi-part Slide-QUOTE REQUEST

Rev 5-13B

Quote: _____ Page: _____ of _____
Company: _____ Distributor #: _____ Door #: _____
Date: _____ Job Name: _____
PO #: _____ Contact: _____
Drop Ship to: _____
Ship Method: _____ Date to Ship: _____

Notes: _____

Type of Unit: Bi-part

GT1175 - drawing # _____
_____ Quantity
_____ Standard _____ Fixed Sidelite
_____ Hurricane _____ Full Open
_____ All-Glass _____ Pocketed
_____ _____ Surface applied (see note 1)
_____ _____ to interior
_____ _____ to exterior
_____ _____ with sidelite
_____ _____ no sidelite
Frame Size:
_____ Width
_____ Header Height (std. = 91-1/2")
_____ Height Including Transom
_____ Number of Verticals in Transom
_____ Clear Door Opening Width

Door/Panel Glass Thickness	Transom Glass Thickness
_____ 1/4" (std.)	_____ 1/4" (std.)
_____ 1/2"	_____ 1/2"
_____ 9/16"	_____ 9/16"
_____ 5/8"	_____ 5/8"
_____ 3/4"	_____ 3/4"
_____ 7/8"	_____ 7/8"
_____ 1"	_____ 1"
_____ Hurricane	

Finish:

_____ Clear (204)
_____ Dk bronze (313)
_____ Special anodize _____
_____ Paint/Clad _____
_____ Prep for paint by distributor

Threshold:

_____ Through Door Opening _____ Under Jambs
_____ Between Jambs _____ Other

Bottom Rail:

_____ Standard _____ 10"
_____ Other _____

Note 1

On surface applied units, indicate the desired location of rocker switches in Notes area at bottom right.

Restrictions:

On hurricane rated sliders not all options are applicable
Refer to worksheets for certain restrictions

Jamb Tubes: _____ None Required

_____ Standard
_____ 1-3/4" x 4-1/2" Single Pocket
_____ 1-3/4" x 4-1/2" Double Pocket
_____ 1-3/4" x 4-1/2" Without Pockets
_____ 1-3/4" x 6-3/8"
_____ 2" x 5"
_____ 2" x 7"
_____ 4-1/2" x 4-1/2" Jamb Tubes
_____ (except All Glass or Telescopic)

Muntin Bars:

_____ 2" std.
_____ 4"
_____ 4-1/2"
_____ 6-3/8"
_____ No muntins required
_____ Special _____
_____ Standard Height 42-1/4" F.F. - top
_____ Special location - F.F. - top
_____ Additional Muntin - F.F. - top
_____ 6-3/8" Muntin Std. - Recessed Panic

Additions/Changes:

_____ Optex x-Zone (in lieu of Acusensor)
_____ Acuvision (in lieu of Acusensor)
_____ Optex i-One (in lieu of Acusensor)
_____ BEA Wizard (in lieu of Acusensor)
_____ Medium Stile (4")
_____ Fail Safe Electric Lock
_____ Fail Secure Electric Lock
_____ Fail Safe Electro-Magnetic Lock
_____ Surface applied push bar exit hardware
_____ Recessed push bar exit hardware
_____ Paddle exit hardware (Fixed Sidelite)
_____ Key Switches in lieu of Rocker Switch
_____ Qty of additional Holding Beams
_____ Reposition access cover to
_____ opposite side of header.
_____ Rail Locks for All Glass Sliders
_____ Include Weathering for All Glass
_____ Prep as Clean Room unit
_____ (except Telescopic or All Glass)
_____ Rocker switches on interior jamb face
_____ _____ Specify LT or RT side.
_____ Aluminum Cart Bars P/N 14-11035
_____ (except All Glass)
_____ (specify which panels to receive bars)
_____ Key cylinder operated flush bolts
_____ (Hurricane unit only)