

Nabco Entrances - Single Slide - **QUOTE REQUEST**

Rev 5-13B

Quote: _____ Page: _____ of _____
Company: _____ Distributor #: _____ Door #: _____
Date: _____ Job Name: _____
PO #: _____ Contact: _____
Drop Ship to: _____
Ship Method: _____ Date to Ship: _____

Notes:

Type of Unit: GT1175 - drawing # _____
_____ Quantity
_____ Bi-part _____ Fixed Sidelite
_____ Single _____ Full Open
_____ _____ Pocketed
_____ Telescopic _____ Surface applied (* see note 1)
_____ All-Glass _____ to interior
_____ Hurricane _____ to exterior
_____ _____ with sidelite
_____ _____ no sidelite

Hand of Unit:
_____ Right hand *viewed from exterior*
_____ Left hand *panic breakaway direction*

Frame Size:
_____ Width
_____ Header Height (std. = 91-1/2")
_____ Height Including Transom
_____ Number of Verticals in Transom
_____ Clear Door Opening Width

Door/Panel Glass Thickness	Transom Glass Thickness
_____ 1/4" (std.)	_____ 1/4" (std.)
_____ 1/2"	_____ 1/2"
_____ 9/16"	_____ 9/16"
_____ 5/8"	_____ 5/8"
_____ 3/4"	_____ 3/4"
_____ 7/8"	_____ 7/8"
_____ 1"	_____ 1"
_____ Hurricane	

Finish:
_____ Clear (204)
_____ Dk bronze (313)
_____ Special anodize _____
_____ Paint/Clad _____
_____ Prep for paint by distributor

Threshold:
_____ Through Door Opening _____ Under Jambs
_____ Between Jambs _____ Other

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at bottom right of this form.

Restrictions:
On hurricane rated sliders not all options are applicable
Refer to worksheets for certain restrictions

Jamb Tubes: _____ None Required
_____ Standard
_____ 1-3/4" x 4-1/2" Single Pocket
_____ 1-3/4" x 4-1/2" Double Pocket
_____ 1-3/4" x 4-1/2" Without Pockets
_____ 1-3/4" x 6-3/8"
_____ 2" x 5"
_____ 2" x 7"
_____ 4-1/2" x 4-1/2" Jamb Tubes
(except All Glass or Telescopic)

Muntin Bars:
_____ 2" std. _____ 4"
_____ 4-1/2" _____ 6-3/8"
_____ 8"
_____ No muntins required
_____ Special _____
_____ Standard Height 42-1/4" F.F. - top
_____ Special location - F.F. - top
_____ Additional Muntin - F.F. - top
_____ 6-3/8" Muntin Std. - Recessed Panic

Bottom Rail:
_____ Standard _____ 10"
_____ Other _____

Additions/Changes:
_____ Optex x-Zone (in lieu of Acusensor)
_____ Acuvision (in lieu of Acusensor)
_____ Optex i-One (in lieu of Acusensor)
_____ BEA Wizard (in lieu of Acusensor)
_____ Medium Stile (4")
_____ Fail Safe Electric Lock
_____ Fail Secure Electric Lock
_____ Fail Safe Electro-Magnetic Lock
_____ Surface applied push bar exit hardware
_____ Recessed push bar exit hardware
_____ Paddle exit hardware (Fixed Sidelite)
_____ Key Switches in lieu of Rocker Switch
_____ Qty. of Additional Holding Beams
_____ Reposition access cover to opposite side of header.
_____ Rail Locks for All Glass Sliders
_____ Include Weathering for All Glass
_____ Prep as Clean Room unit

_____ Rocker switches on interior jamb face
_____ Specify LT or RT side.
_____ Aluminum Cart Bars P/N 14-11035
(specify which panels to receive bars)
_____ Key cylinder operated flush bolts
(Hurricane unit only)