

Nabco Entrances - Telescopic Slide - **ORDER FORM**

Rev 5-13

Order _____ Page: _____ of _____
 Company: _____ Distributor #: _____ Door #: _____
 Date: _____ Job Name: _____
 PO #: _____ Contact: _____
 Drop Ship to: _____
 Ship Method: _____ Date to Ship: _____

Notes:

Type of Unit: GT1175 - drawing # _____
 _____ Quantity
 _____ Bi-part _____ Fixed Sidelite
 _____ Single _____ Full Open
 _____ Surface applied (* see note 1)
 _____ to interior
 _____ to exterior
 _____ with sidelite
 _____ no sidelite

Hand of Unit:
 _____ Right hand *view from exterior*
 _____ Left hand *panic breakaway direction*

Frame Size:
 _____ Width
 _____ Header Height (std. = 91-1/2")
 _____ Height Including Transom
 _____ Number of Verticals in Transom
 _____ Clear Door Opening Width

Door/Panel Glass Thickness	Transom Glass Thickness
_____ 1/4" (std.)	_____ 1/4" (std.)
_____ 1/2"	_____ 1/2"
_____ 9/16"	_____ 9/16"
_____ 5/8"	_____ 5/8"
_____ 3/4"	_____ 3/4"
_____ 7/8"	_____ 7/8"
_____ 1"	_____ 1"

Finish:
 _____ Clear (204)
 _____ Dk bronze (313)
 _____ Special anodize _____
 _____ Paint/Clad _____
 _____ Prep for paint by distributor

Threshold: (see note 2)
 _____ Through Door Opening _____ Under Jamb
 _____ Between Jamb _____ Other

Jamb Tubes:
 _____ Standard (2" x 7")
 _____ No Jamb Required

Muntin Bars:
 _____ 2" std. _____ 6-3/8"
 _____ 4" _____ 4-1/2"
 _____ No muntins required
 _____ Special _____
 _____ Standard Height 42-1/4" F.F. - top
 _____ Special location - F.F. - top
 _____ Additional Muntin - F.F. - top
 _____ 6-3/8" Muntin Std. - Recessed Panic

Bottom Rail:
 _____ Standard _____ 10"
 _____ Other _____

Additions:
 _____ Acuvision (in lieu of Acusensor)
 _____ Optex i-One (in lieu of Acusensor)
 _____ Optex X-Zone (in lieu of Acusensor)
 _____ BEA Wizard (in lieu of Acusensor)
 _____ Medium Stile (4")
 _____ Fail Safe Electric Lock
 _____ Fail Secure Electric Lock
 _____ Fail Safe Electro-Magnetic Lock
 _____ Surface applied push bar exit hardware
 _____ Recessed push bar exit hardware
 _____ Paddle exit hardware (Fixed Sidelite)
 _____ Key Switches in lieu of Rocker Switch
 _____ Qty of additional Holding Beams
 _____ Rocker switches on interior jamb face
 _____ Specify LT or RT side.

Note 2: Threshold jamb to jamb is necessary on a full open unit. Any threshold option is available for fixed units.

Note 1:
 Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. We rip the hook off the cover on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on. If you would like to change the location of the control switches, indicate the desired location in the Notes area at the right.