

Nabco Entrances - GT1400 Fold Door - QUOTE REQUEST

Rev 5-13

Quote _____ Date to ship: _____
 Company: _____ Distributor #: _____ Door #: _____
 Date: _____ Job Name: _____
 PO #: _____ Contact: _____
 Ship to: _____
 Freight Carrier: _____

Notes:

GT1400 - _____ drawing #: _____

Type of Unit:

_____ Quantity
 _____ Single Fold *Door folds and breaks*
 _____ Bi-Fold *open in the same direction*

Hand of Unit:

_____ Right hand
 _____ Left hand
Viewed from non-folding side (interior)

Frame Size:

_____ Width
 _____ Header Height (std. = 91-1/2")
 _____ Height Including Transom
 _____ Number of Verticals in Transom
 _____ Clear Door Opening Width

	Min Width	Max Width
Bi-Fold	76"	108"
Single Fold	46"	63"

Door/Panel Glass Thickness

_____ 1/4" (std.)
 _____ 1/2"
 _____ 9/16"
 _____ 5/8"
 _____ 3/4"
 _____ 7/8"
 _____ 1"
 _____ Hurricane

Transom Glass Thickness

_____ 1/4" (std.)
 _____ 1/2"
 _____ 9/16"
 _____ 5/8"
 _____ 3/4"
 _____ 7/8"
 _____ 1"

Finish:

_____ Clear (204)
 _____ Dk bronze (313)
 _____ Special anodize _____
 _____ Paint/Clad _____
 _____ Prep for paint by distributor

Guide Rails:

_____ (Qty.) Fold Side (matches finish of door)

Length: _____ One Way Traffic (per ANSI 156.10)
 Length: _____ Two Way Traffic (per ANSI 156.10)
 Length: _____ Other (as specified)

Jamb Tubes:

_____ Standard
 _____ 1-3/4" x 6-3/8"
 _____ 2" x 7"
 _____ No Jambs Required

Muntin Bars:

_____ 2" std.
 _____ 4"
 _____ 4-1/2"
 _____ 6-3/8"
 _____ No muntins required
 _____ Special _____
 _____ Standard Height 42-7/8" F.F. - top
 _____ Special location - F.F. - top
 _____ Additional Muntin - F.F. - top

Bottom Rail:

_____ Standard
 _____ 10"
 _____ Other _____

Additional Sensors:

Header Mounted Sensors:
 _____ (Qty.) Acusensor
 _____ (Qty.) BEA Wizard
 _____ (Qty.) Optex i-One
 _____ (Qty.) Optex Reaction2

Locks:

_____ Manual - manual lock(s) with thumb
 turn and key cylinder (standard)
 _____ Flush Bolt - lock(s) at fold point(s)
 _____ No Cylinder or Flush Bolts
 _____ Electro-Magnetic Lock (fail-safe)

Threshold:

_____ Threshold

On Hurricane Units:

- 1 Transoms are not available
- 2 Muntin bars are not available
- 5 Four inch rails only
- 6 Glass stops for 9/16 inch glass only
- 7 Flush bolts are standard
- 8 Units heights are limited to 91-1/2 inches
- 3 Frame widths on singles limited to 48 inches or less
- 4 Frame widths on bifolds limited to 96 inches or less