

# Nabco Entrances - GT1400 Fold Door - ORDER FORM

Rev 5-13

Order \_\_\_\_\_ Date to ship: \_\_\_\_\_  
 Company: \_\_\_\_\_ Distributor #: \_\_\_\_\_ Door #: \_\_\_\_\_  
 Date: \_\_\_\_\_ Job Name: \_\_\_\_\_  
 PO #: \_\_\_\_\_ Contact: \_\_\_\_\_  
 Ship to: \_\_\_\_\_  
 Freight Carrier: \_\_\_\_\_

**Notes:**

GT1400 - \_\_\_\_\_ drawing #: \_\_\_\_\_

**Type of Unit:**

\_\_\_\_\_ Quantity  
 \_\_\_\_\_ Single Fold *Door folds and breaks*  
 \_\_\_\_\_ Bi-Fold *open in the same direction*

**Jamb Tubes:**

\_\_\_\_\_ Standard  
 \_\_\_\_\_ 1-3/4" x 6-3/8"  
 \_\_\_\_\_ 2" x 7"  
 \_\_\_\_\_ No Jamb's Required

**Hand of Unit:**

\_\_\_\_\_ Right hand  
 \_\_\_\_\_ Left hand  
*Viewed from non-folding side (interior)*

**Muntin Bars:**

\_\_\_\_\_ 2" std.  
 \_\_\_\_\_ 4"  
 \_\_\_\_\_ 4-1/2"  
 \_\_\_\_\_ 6-3/8"  
 \_\_\_\_\_ No muntins required  
 \_\_\_\_\_ Special \_\_\_\_\_  
 \_\_\_\_\_ Standard Height 42-7/8" F.F. - top  
 \_\_\_\_\_ Special location - F.F. - top  
 \_\_\_\_\_ Additional Muntin - F.F. - top

**Frame Size:**

\_\_\_\_\_ Width  
 \_\_\_\_\_ Header Height (std. = 91-1/2")  
 \_\_\_\_\_ Height Including Transom  
 \_\_\_\_\_ Number of Verticals in Transom  
 \_\_\_\_\_ Clear Door Opening Width

	Min Width	Max Width
Bi-Fold	76"	108"
Single Fold	46"	63"

**Bottom Rail:**

\_\_\_\_\_ Standard  
 \_\_\_\_\_ 10"  
 \_\_\_\_\_ Other \_\_\_\_\_

**Door/Panel Glass Thickness**

\_\_\_\_\_ 1/4" (std.)  
 \_\_\_\_\_ 1/2"  
 \_\_\_\_\_ 9/16"  
 \_\_\_\_\_ 5/8"  
 \_\_\_\_\_ 3/4"  
 \_\_\_\_\_ 7/8"  
 \_\_\_\_\_ 1"  
 \_\_\_\_\_ Hurricane

**Transom Glass Thickness**

\_\_\_\_\_ 1/4" (std.)  
 \_\_\_\_\_ 1/2"  
 \_\_\_\_\_ 9/16"  
 \_\_\_\_\_ 5/8"  
 \_\_\_\_\_ 3/4"  
 \_\_\_\_\_ 7/8"  
 \_\_\_\_\_ 1"

**Additional Sensors:**

Header Mounted Sensors:  
 \_\_\_\_\_ (Qty.) Acusensor  
 \_\_\_\_\_ (Qty.) BEA Wizard  
 \_\_\_\_\_ (Qty.) Optex i-One  
 \_\_\_\_\_ (Qty.) Optex Reaction2

**Finish:**

\_\_\_\_\_ Clear (204)  
 \_\_\_\_\_ Dk bronze (313)  
 \_\_\_\_\_ Special anodize \_\_\_\_\_  
 \_\_\_\_\_ Paint/Clad \_\_\_\_\_  
 \_\_\_\_\_ Prep for paint by distributor

**Locks:**

\_\_\_\_\_ Manual - manual lock(s) with thumb  
 tum and key cylinder (standard)  
 \_\_\_\_\_ Flush Bolt - lock(s) at fold point(s)  
 \_\_\_\_\_ No Cylinder or Flush Bolts  
 \_\_\_\_\_ Electro-Magnetic Lock (fail-safe)

**Threshold:**

\_\_\_\_\_ Threshold

**Guide Rails:**

\_\_\_\_\_ (Qty.) Fold Side (matches finish of door)

Length: \_\_\_\_\_ One Way Traffic (per ANSI 156.10)  
 Length: \_\_\_\_\_ Two Way Traffic (per ANSI 156.10)  
 Length: \_\_\_\_\_ Other (as specified)

**On Hurricane Units:**

- 1 Transoms are not available
- 2 Muntin bars are not available
- 5 Four inch rails only
- 6 Glass stops for 9/16 inch glass only
- 7 Flush bolts are standard
- 8 Units heights are limited to 91-1/2 inches
- 3 Frame widths on singles limited to 48 inches or less
- 4 Frame widths on bifolds limited to 96 inches or less