

Gyro Tech GT1500 Convenience Window- **ORDER FORM**

Rev 5-13

Order _____

Company: _____

Distributor #: _____ Door #: _____

Date: _____

Job Name: _____

PO #: _____

Contact: _____

Drop Ship to: _____

Ship Method: _____ Date to Ship: _____

Notes:

Type of Unit: GT1500 - _____ (architectural drawing #)

_____ Quantity

Mode:

_____ Bi-part

_____ Automatic

_____ Single

_____ Manual

Hand of Unit:

_____ Right hand *viewed from exterior*

_____ Left hand

Additions:

_____ Holding Beam/s
Qty: _____

Frame Size:

_____ Width (min. 30" singles - 42" Bi-parts)
 _____ Header Height without Transom (std. = 35-3/4") (min. 30")
 _____ Height Including Transom
 _____ Number of Verticals in Transom

_____ Armored Strike
 _____ "D" Handle in lieu of Recessed
 on Interior Panels (P/N 21-3754)
 _____ "4570" Handle in lieu of Recessed
 on Interior Panels (P/N P/N 14-10588)

Sliding/Fixed Panel

Glass Thickness

_____ 1/4" (std.)
 _____ 1/2"
 _____ 9/16"
 _____ 5/8"
 _____ 3/4"
 _____ 7/8"
 _____ 1"

Transom Glass Thickness

_____ 1/4" (std.)
 _____ 1/2"
 _____ 9/16"
 _____ 5/8"
 _____ 3/4"
 _____ 7/8"
 _____ 1"

Finish:

_____ Clear (204)
 _____ Dk bronze (313)
 _____ Special anodize _____
 _____ Paint/Clad _____
 _____ Prep for paint by distributor