

# Nabco Entrances - Manual/ICU - QUOTE REQUEST

Rev 5-13a

Quote \_\_\_\_\_ Page: \_\_\_\_\_ of \_\_\_\_\_

Company: \_\_\_\_\_ Distributor #: \_\_\_\_\_ Door Number: \_\_\_\_\_

Date: \_\_\_\_\_ Job Name: \_\_\_\_\_

PO #: \_\_\_\_\_ Contact: \_\_\_\_\_

Ship to: \_\_\_\_\_

Freight Carrier: \_\_\_\_\_ Job Name: \_\_\_\_\_ Ship Date: \_\_\_\_\_

ENTER "X" TO INDICATE A SELECTION

Notes:

**Type of Unit:**

\_\_\_\_\_ Quantity

**Model:**

|                |                |                |
|----------------|----------------|----------------|
| _____ GT2100R  | _____ GT2125R  | _____ GT2150R  |
| _____ GT2100L  | _____ GT2125L  | _____ GT2150L  |
| _____ GT2100TR | _____ GT2125TR | _____ GT2150TR |
| _____ GT2100TL | _____ GT2125TL | _____ GT2150TL |
| _____ GT2100B  | _____ GT2125B  | _____ GT2150B  |
| _____ GT2100TB | _____ GT2125TB | _____ GT2150TB |

**Frame Size:**

\_\_\_\_\_ Width  
 \_\_\_\_\_ Header Height (std. = 88")  
 \_\_\_\_\_ Height Including Transom  
 \_\_\_\_\_ Number of Verticals in Transom  
 \_\_\_\_\_ Clear Door Opening Width

**Door/Panel Glass Thickness**

\_\_\_\_\_ 1/4" (std.)  
 \_\_\_\_\_ 1/2"  
 \_\_\_\_\_ 9/16"  
 \_\_\_\_\_ 5/8"  
 \_\_\_\_\_ 3/4"  
 \_\_\_\_\_ 7/8"  
 \_\_\_\_\_ 1"

**Transom Glass Thickness**

\_\_\_\_\_ 1/4" (std.)  
 \_\_\_\_\_ 1/2"  
 \_\_\_\_\_ 9/16"  
 \_\_\_\_\_ 5/8"  
 \_\_\_\_\_ 3/4"  
 \_\_\_\_\_ 7/8"  
 \_\_\_\_\_ 1"

**Finish:**

\_\_\_\_\_ Clear (204)  
 \_\_\_\_\_ Dk bronze (313)  
 \_\_\_\_\_ Special anodize  
 \_\_\_\_\_ Paint/Clad  
 \_\_\_\_\_ Prep for paint by distributor

**Threshold: (applies to 2100 or 2150 only)**

\_\_\_\_\_ Through Door Opening  
 \_\_\_\_\_ Between Jambes  
 \_\_\_\_\_ Under Jambes  
 \_\_\_\_\_ Other

**Jamb Tubes:**

\_\_\_\_\_ Standard  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Without Pockets  
 \_\_\_\_\_ 1-3/4" x 6-3/8"  
 \_\_\_\_\_ 2" x 5"  
 \_\_\_\_\_ 2" x 7"  
 \_\_\_\_\_ No Jambes Required

**Muntin Bars:**

\_\_\_\_\_ 2" std.  
 \_\_\_\_\_ 4"  
 \_\_\_\_\_ 6-3/8"  
 \_\_\_\_\_ 8"  
 \_\_\_\_\_ No muntins required  
 \_\_\_\_\_ Standard Height 42-1/4" F.F. - top  
 \_\_\_\_\_ Special location - F.F. - top  
 \_\_\_\_\_ Additional Muntin - F.F. - top

**Bottom Rail:**

\_\_\_\_\_ Standard  
 \_\_\_\_\_ 6-1/2"  
 \_\_\_\_\_ 10"

**Options:**

\_\_\_\_\_ Recessed Handles (both sides)  
 \_\_\_\_\_ 4570 (Levers down - Positive latch)  
 \_\_\_\_\_ Handle + Recessed Pull  
 \_\_\_\_\_ Handle on Both Sides  
 \_\_\_\_\_ (reduces door opening)  
 \_\_\_\_\_ Medium Stile  
 \_\_\_\_\_ No Panic Breakout  
 \_\_\_\_\_ Delete Sidelites for Surface Applied  
 \_\_\_\_\_ Floor Sweeps  
 \_\_\_\_\_ Pile + Brush Weather Stripping  
 \_\_\_\_\_ NUDO Panels in bottom of doors  
 \_\_\_\_\_ Self Closing  
 \_\_\_\_\_ Hold Open