NABCO Entrances - Manual/ICU Door - Shop Drawing F Rev 1-2015

Page: _____ of _____

Company: _____ Distributor #: _____ Door Number: _____

Date: _____ Job Name: _____

_____ Contact: _____

_____

ENTER "X" TO INDICATE A SELECTION

Notes:

Type of Unit:

_____ Quantity

Model:

_____ GT2100R	_____ GT2125R	_____ GT2150R
_____ GT2100L	_____ GT2125L	_____ GT2150L
_____ GT2100TR	_____ GT2125TR	_____ GT2150TR
_____ GT2100TL	_____ GT2125TL	_____ GT2150TL
_____ GT2100B	_____ GT2125B	_____ GT2150B
_____ GT2100TB	_____ GT2125TB	_____ GT2150TB

Frame Size:

_____ Width
_____ Header Height (std. = 88")
_____ Height Including Transom
_____ Number of Verticals in Transom
_____ Clear Door Opening Width

Door/Panel Glass Thickness

_____ 1/4" (std.)
_____ 1/2"
_____ 9/16"
_____ 5/8"
_____ 3/4"
_____ 7/8"
_____ 1"

Transom Glass Thickness

_____ 1/4" (std.)
_____ 1/2"
_____ 9/16"
_____ 5/8"
_____ 3/4"
_____ 7/8"
_____ 1"

Finish:

_____ Clear (204)
_____ Dk bronze (313)
_____ Special anodize
_____ Paint/Clad
_____ Prep for paint by distributor

_____
_____

Threshold: (applies to 2100 or 2150 only)

_____ Through Door Opening
_____ Between Jambs
_____ Under Jambs
_____ Other

Jamb Tubes:

_____ Standard
_____ 1-3/4" x 4-1/2" Without Pockets
_____ 1-3/4" x 6-3/8"
_____ 2" x 5"
_____ 2" x 7"
_____ No Jambs Required

Muntin Bars:

_____ 2" std.
_____ 4"
_____ 6-3/8"
_____ 8"
No muntins required

_____ Standard Height 42-1/4" F.F. - top
_____ Special location - F.F. - top
_____ Additional Muntin - F.F. - top

Bottom Rail:

_____ Standard
_____ 6-1/2"
_____ 10"

Options:

_____ Recessed Handles (both sides)
_____ 4570 (Levers down - Positive latch)
_____ Handle + Recessed Pull
_____ Handle on Both Sides (reduces door opening)
_____ Medium Stile
_____ No Panic Breakout
_____ Delete Sidelites for Surface Applied
_____ Floor Sweeps
_____ Pile + Brush Weather Stripping
_____ NUDO Panels in bottom of doors
_____ Self Closing
_____ Hold Open