## GT2300 Manual/ICU Swing Door - QUOTE REQUEST

Qu	ote:		Rev 5-13	
Company:		Distributor #:	Door #:	
Date:		Job Name:		
PO #:		Contact:		
Ship to:				
Freight Carrier:	Qty	Required:	1	
	ENTER "X" TO INDICATE A	SELECTION		
S:				
·.				
Type of Unit:	t: Quantity		Jamb Tubes:	
		Standard (1-3/4" x 4-1/2" - No Pockets)		
Model Type "A" or "B" as view "A" Inactive Door -			4" x 6-3/8"	
		2" x	j	
"B" Active Door - Inactive Door		2" x	<u>_</u>	
F 0:			Jambs Required	
Frame Size:	) (OO 4/0   Massissassa)	неа	der Width for No Jambs	
	ors) (99 1/2" Maximum)	Manda Bass		
Header Height (Standard 87-5/8", Maximum 125")  Active door width (panel equipped with Latch Handle)		Muntin Bars:		
		2" st	td.	
Inactive door width (panel equipped with Flush Bolt)		·		
Door/Panel Glass Thickness		6-3/8" 8"		
	•			
1/4" (std.) 1" or other		No r	muntins required	
i or other		Muntin Hoight		
Finish.		Muntin Height:	adord Hoight 42 1/4" F. F. Ton	
Finish:		Standard Height 42-1/4" F.F Top  Special location - F.F Top		
Clear (204)			itional Muntin - F.F Top	
Dk bronze (313)		Addi	itional Muntin - F.F Top	
Special anodize		Ontions		
Prep for paint by distributor		Options:	iuma Ctila	
FIEP FOI PAINT BY CISTINGTOI			ium Stile oke Rated Regiured	
Threshold:			Some Options Affect Smoke Rating	
No Threshold	Hadar Jamba	Some Options A	Trect Smoke Rating	
(Standard)	Under Jambs	NULF	O Demole	
	(Included in Height)	NUL	OO Panels	
Between Jambs	Other	Check	All Lites	
Dattam Baile	Ton Doile	One	Bottom Lites	
Bottom Rail:	Top Rail:		Top Lites  Motallia Silver	
4" (Standard)	4" (Standard)	Chassa	Metallic Silver	
5"	5"	Choose Color	Bone White	
6-1/2"	6-1/2"	Coloi	Glossy White	
10"	10"	01:	Dark Bronze	
		Choose	Textured	
		Finish	Smooth	

Page 1 OF 1

Note: Door gap at bottom is 1/2" standard