

NABCO GT710/8710

Low Energy ADA Swing Door Operators



NABCO 

Great for the Following Applications:

- Airports & Transportation, Grocery & Retail, Healthcare, Hospitality, Malls, Schools, and many other applications

Hydraulic design offers proven reliability

- Adjustable closing speeds to enhance energy savings
- Manual mode requires very little pressure to open promoting ease of operation
- Approved on fire door assemblies rated up to 3 hours, maintaining security and safety
- Hydraulic back-check during windy conditions protects the door and operator from damage
- 35 years of history as a tried and trusted Low Energy Operator device that can be surface mounted almost anywhere
- Good Indoor/Interior Option, where traffic flow is typically the door manually.

NABCO GT710/8710

Low Energy ADA Swing Door Operator

The NABCO GT710/8710 Low Energy Operator is engineered for interior and exterior use, and designed to automate essentially any new or existing door frame. The GT710/8710 operates in both automatic and manual modes with a hydraulic back-check that protects the door and mechanical operator from damage when forced open in windy conditions or when manually operated. The GT710/8710 Operator has been approved for use on fire door assemblies rated up to three hours. The low energy performance, combined with the adjustable opening and closing speeds, reduces energy consumed, which offers a prompt return on your investment.

Passed the ONE-MILLION CYCLE COUNT Endurance Test

Product Information	
Header dimensions	Curved Header (GT710) - 5" H X 5 3/4" D Squared Header (GT8710) - 6" H X 5 1/2" D
Standard finish	Clear, black, or dark bronze anodized
Optional finishes	Painted, clad, or special anodized
Mounting	Surface-applied or overhead concealed
Installation types	Push or pull
Operating voltage	120 VAC @ <5 amps
Auxiliary power output	12VDC 750mA
Operator drive	Electro-hydraulic
Motor voltage	Pulse width modulated
Motor type	1/8th HP @ peak
Control type	Microprocessor
Door panel weight	300 lbs.
Adjustable open	Force and speed
Adjustable close	Force and speed
Closing method	Spring/hydraulic (with selectable power assist)
Adjustable opening angle	Up to 145°
Power boost close	Selectable
Basic features	Low-energy operation Push and go Obstacle detection in opening and closing cycles Sequential or timer mode operation LCD screen for programming and diagnostics Open- or closed-circuit safety inputs Momentary or maintained activation
Switch modes	On, off, hold-open
Opening and closing speed	Adjustable
Hold-open time	Adjustable (0-30 seconds)
Code compliances	ANSI A156.19/ANSI A117.1
Approvals	UL, ULc



GT710 Operator with Curved Header



Sim Pair GT8710 Operators with Square Headers

Available Configurations:

- Single-door
- Simultaneous Pair
- Dual-egress
- Opman



**Design Your New facility
with NABCO Doors**

Visit:

NABCOEntrances.com/products/swing-door-operators/



Member of the **Nabtesco** Group



NABCO Entrances Inc.
S82 W18717 Gemini Drive
Muskego, WI 53150
nabcoentrances.com
info@nabcoentrances.com
P 877-622-2694

Rev. 4-11-2025