

NABCO Entrances GT-2300 Manual/ICU Swing Door - Shop Drawing Request

Company: _____
 Date: _____

Distributor #: _____ Door #: _____
 Job Name: _____
 Contact: _____

ENTER "X" TO INDICATE A SELECTION

Notes:

Type of Unit: _____ **Quantity** _____

Model Type "A" or "B" as viewed from swing side:

_____ "A" Inactive Door - Active Door
 _____ "B" Active Door - Inactive Door

Frame Size:

_____ Width (Frame & Doors) (99 1/2" Maximum)
 _____ Header Height (Standard 87-5/8", Maximum 125")
 _____ Active door width (panel equipped with Latch Handle)
 _____ Inactive door width (panel equipped with Flush Bolt)

Door/Panel Glass Thickness

_____ 1/4" (std.)
 _____ 1" or other

Finish:

_____ Clear (204)
 _____ Dk bronze (313)
 _____ Special anodize
 _____ Paint/Clad
 _____ Prep for paint by distributor

Threshold:

_____ No Threshold (Standard)	_____ Under Jambs (Included in Height)
_____ Between Jambs	_____ Other

Bottom Rail:

_____ 4" (Standard)
 _____ 5"
 _____ 6-1/2"
 _____ 10"

Top Rail:

_____ 4" (Standard)
 _____ 5"
 _____ 6-1/2"
 _____ 10"

Note: Door gap at bottom is 1/2" standard

Jamb Tubes:

_____ Standard (1-3/4" x 4-1/2" - No Pockets)
 _____ 1-3/4" x 6-3/8" } Hinges are on
 _____ 2" x 5" } outside edges
 _____ 2" x 7" } of jamb tubes
 _____ No Jambs Required
 _____ Header Width for No Jambs

Muntin Bars:

_____ 2" std.
 _____ 4"
 _____ 6-3/8"
 _____ 8"
 _____ No muntins required

Muntin Height:

_____ Standard Height 42-1/4" F.F. - Top
 _____ Special location - F.F. - Top
 _____ Additional Muntin - F.F. - Top

Options:

_____ Medium Stile
 _____ Smoke Rated Required
 Some Options Affect Smoke Rating

NUDO Panels

Check One	_____ All Lites
	_____ Bottom Lites
	_____ Top Lites
Choose Color	_____ Metallic Silver
	_____ Bone White
	_____ Glossy White
	_____ Dark Bronze
Choose Finish	_____ Textured
	_____ Smooth

Standard 1-3/4" x 4-1/2" (no pockets)