


- NOTES:**
1. STANDARD FINISH AVAILABLE IN WHITE PAINTED ALUMINUM AND BRUSHED SS.
  2. FOR A STAINLESS STEEL DOOR LEAF THERE IS A VERTICAL JOINT LINE WHEN THE DOOR WIDTH IS OVER 43 5/16".
  3. DUAL HOLDING BEAMS AT 21" AND 51" ARE STANDARD.
  4. POWER TO HEADER WILL BE 115VAC, 5 AMP PER OPERATOR PROVIDED BY ELECTRICAL CONTRACTOR.
  5. AIRTIGHTNESS PERFORMANCE: Class A-4.
  6. SOUND INSULATION PERFORMANCE: Class T-1.
  7. LEAD THICKNESS IN PANEL - 2mm
  8. OPTIONAL THRESHOLD AVAILABLE
  9. RECESSED PULL HANDLE IS STANDARD. TUBULAR PULL HANDLES ARE NOT AVAILABLE ON THIS DOOR



NABCO Entrances Inc.  
 S82 W18717 Gemini Drive Muskego, WI 53150  
 www.nabcoentrances.com 1-877-622-2694

JOB NAME: \_\_\_\_\_  
 LOCATION: \_\_\_\_\_  
 DISTRIBUTOR: \_\_\_\_\_  
 DOOR #: \_\_\_\_\_ DATE: \_\_\_\_\_  
 SHEET \_\_\_\_\_ OF \_\_\_\_\_

**GT9300-SX-L**  
**LEAD LINED**  
**HERMETIC**  
**DOOR**  
 SINGLE SLIDE  
 LEFT HAND