

## **TECHNICAL BULLETIN**

S82 W18717 Gemini Drive Muskego, WI, 53150 Phone: (877) 622-2694, Fax: (888) 679-3319 www.NABCOEntrances.com Date: October 20, 2017

Who is the contact? Technical Support Department

## "ACUVISION" SENSORS NO LONGER AVAILABLE

With sensor monitoring becoming part of the new ANSI standard, the Acuvision sensor will no longer be available. The Acusensor M will now replace the Acuvision as the standard safety sensor on any unit where the Acuvision was being used including:

- Over-head presence on swing door operators
- Over-head presence on GT1400 folding doors
- On GT1175 sliding doors

## With the addition of monitoring functions, the Acusensor M has all the features of the Acuvision including:

- Active infrared for approach and presence
- Able to look back through the threshold
- Multi-color LEDs to show sensor's status
- Suitable for sliding, swinging, and folding doors
- Detection depth can be increased with an angled spacer (sold separately)
- Accommodates new installations or sensor upgrades
- All features comply with existing and upcoming ANSI A156.10 requirements

NABCO is already making the transition to the Acusensor M.

- New Acusensor M part numbers:
- Sensor package (without spacer): A-01306
- (includes sensor, black cover, modified harness)
- Angled Spacer: V-00742
- Sensor Only (with black cover): V-00741
- Replacement cover (black): V-00744
- Replacement cover (silver): V-00743
- Harness only: A-01292

## Bulletin Number: 88