

Nabco Entrances - Bi-part Slide Door - ORDER FORM

Rev. 2018

Quote: _____ Page: _____ of _____
 Company: _____ Distributor #: _____ Door #: _____
 Date: _____ Job Name: _____
 PO #: _____ Contact: _____
 Drop Ship to: _____
 Ship Method: _____ Date to Ship: _____

Notes:

Type of Unit: GT1175 - drawing # _____

_____ Quantity

_____ Bi-part _____ Fixed Sidelite

_____ Single _____ Full Open

_____ _____ Pocketed

_____ Telescopic

_____ All-Glass (FSL Only)

_____ Surface applied (* **see note 1**) { _____ to interior
 _____ to exterior
 _____ w/ sidelite
 _____ no sidelite

Custom Surface Applied Units:

_____ Surface Applied to Exterior with Wall Track

_____ Surface Applied to Interior, Breakout Thru Opening

(Wall Opening required to size doors correctly)

_____ x _____ Wall Opening (W x H)

Hand of Unit:_____ Right hand *viewed from exterior*_____ Left hand *panic breakaway direction***Frame Size:**

_____ Width _____ Header Height (std. = 91-1/2")

_____ Height Including Transom

_____ Number of Verticals in Transom

_____ Clear Door Opening Width

Door/Panel Glass Thickness

_____ 1/4" (std.)

_____ 1/2"

_____ 9/16"

_____ 5/8"

_____ 3/4"

_____ 7/8"

_____ 1"

Transom Glass Thickness

_____ 1/4" (std.)

_____ 1/2"

_____ 9/16"

_____ 5/8"

_____ 3/4"

_____ 7/8"

_____ 1"

Finish:

_____ Clear (204) _____ Dk bronze (313)

_____ Special anodize _____

_____ Paint/Clad _____

_____ Prep for paint by distributor

Threshold:

_____ Through Door Opening _____ Under Jambs

_____ Between Jambs _____ Other

Bottom Rail:

_____ Standard _____ 10" _____ Other

Jamb Tubes: _____ None Required

_____ Standard ~ 1-3/4" x 4-1/2"

_____ 1-3/4" x 4-1/2" Single Pocket

_____ 1-3/4" x 4-1/2" Double Pocket

_____ 1-3/4" x 4-1/2" Without Pockets

_____ 1-3/4" x 6-3/8"

_____ 2" x 5"

_____ 2" x 7"

_____ 4-1/2" x 4-1/2" Jamb Tubes (*see below*)

except AG or Telescopic

Muntin Bars:

_____ 2" std. _____ 4"

_____ 8" _____ 6-3/8"

_____ No muntins required

_____ Special _____

_____ Standard Height 42-1/4" F.F. - top

_____ Special location - F.F. - top

_____ Additional Muntin - F.F. - top

_____ 6-3/8" Muntin Std. - Recessed Panic

Additions/Changes:

_____ Acuzone (in lieu of Acusensor M)

_____ Optex i-One (in lieu of Acusensor M)

_____ BEA IXIO-DT1 (in lieu of Acusensor M)

_____ Optex OA Axis (in lieu of Acusensor M)

_____ Medium Stile (4")

_____ Fail Safe Electric Lock

_____ Fail Secure Electric Lock

_____ Fail Safe Electro-Magnetic Lock

_____ Surface applied push bar exit hardware

_____ Recessed push bar exit hardware

_____ Paddle exit hardware (Fixed Sidelite)

_____ Key Switches in lieu of Rocker Switch

_____ Additional Holding Beams - Qty: _____

_____ Access cover on opposite side of header

_____ Rail Locks for All Glass Sliders

_____ Include Weathering for All Glass

_____ Prep as Clean Room unit

(except Telescopic or All Glass)

_____ Rocker switches at location OTHER

than on interior jamb face

(include diagram with order)

_____ Aluminum Cart Bars Pt # 14-11035

(except All Glass)

(specify which panels to receive bars)

_____ Additional sidelite/s

_____ Width

_____ Height

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form. Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. We rip the hook off the cover on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on.