4550 Dead Bolt Lever with Exit Indicator

Delete Sidelites for Surface Applied

Composite panels in bottom of doors

Pile + Brush Weather Stripping

Medium Stile

Floor Sweeps

Self Closing Hold Open

No Panic Breakout

Nabco	Entrances - Ma	nual/ICU Doo	r - <u>ORDER</u>	<u>FORM</u>	Rev. 2018
Quote:				Page:	of
Company:			[Distributor #:	Door #:
Date:			 Job Name:		
PO #:			Contact:		
Drop Ship	to:				
Ship Method:			Da	te to Ship:	
		ENTER "X" T	O INDICATE A SI	ELECTION	
Notes:					
Type of Un	nit: _Quantity			Jamb Tubes:	
Model:					x 4-1/2" Without Pockets x 6-3/8"
	GT2100R	GT2125R	GT2150R	2" x 5"	
	GT2100L	GT2125L	GT2150L	2" x 7"	
	GT2100TR GT2100TL	GT2125TR GT2125TL	GT2150TR GT2150TL	No Jan	nbs Required
	GT2100TL	GT21251L	GT21501L GT2150B		
	GT2100B	GT2125TB	GT2150TB	Muntin Bars:	
				2" std.	
Frame Size: Width Header Height (slider std. = 88")				4"	
				6-3/8"	
				8"	
	_ Height Including Transor			No mu	ntins required
	Number of Verticals in Transom			Ctondo	and Hainbt 40 4/4" F.F. tan
	_Clear Door Opening Wid	iui			ard Height 42-1/4" F.F top
Door/Panel Glass Thickness Transom Glass Thickness			Thickness	Special location - F.F top Additional Muntin - F.F top	
		1/4" (st		Additio	יוומו ויוונווווו - Γ.Γ ιυρ
	_ 1/4 (Std.) 1/2"	1/2"	u. <i>)</i>	Options:	
	_ 1/2 _ 9/16"	9/16"		Options.	
	_ 9/10 _ 5/8"	5/8"		(Standard pulls are	the "D" and recessed pulls)
		3/4"			sed Handles (both sides)
	- ^{3/4} 7/8"	7/8"			Levers Down - Positive Latch)
	- 1"	1"			Handle + Recessed Pul
	_				Handle on Both Sides
Finish:	Dk bronze (313)	Clear (2		•	es door opening on 2100 only CU Flush Lockset

Under Jambs

Other

Threshold:

Bottom Rail:

Prep for paint by distributor

(applies to 2150 only)

Through Door Opening

Special anodize

Between Jambs

Paint/Clad