

Nabco Entrances - GT 1175 Hurricane Models H60 or H105 Order Form

Rev. 2019

Order _____ Quote _____ Page: _____ of _____
 Company: _____ Distributor #: _____ Door #: _____
 Date: _____ Job Name: _____
 PO #: _____ Contact: _____
 Drop Ship to: _____
 Ship Method: _____ Date to Ship: _____

Notes:

_____ **H105** _____ **Impact**
 _____ **H60** _____ **Non-Impact**

Type of Unit:

_____ Quantity _____ Fixed Sidelite
 _____ Bi-part _____ Full Open
 _____ Single

Muntin Bars:

_____ 4" (H105 only)

Hand of Unit:

_____ Right hand *viewed from exterior*
 _____ Left hand *panic breakaway direction*

Bottom Rail:

_____ 4"	H60
_____ 6.5"	
_____ 10"	
_____ 6.5"	H105
_____ 10"	

Frame Size:

_____ Width ((H60 max. 16' / H105 max. 18'))
 _____ Header Height less transom (see below)
 _____ **H60** max. 7' 7-1/2" **H105** max. 8' 8"
 _____ Clear Door Opening Width

Note:

All hurricane units are equipped with 1/2" jamb to jamb thresholds.

Additions/Changes:

_____ Acuzone (in lieu of Acusensor)
 _____ Optex i-One (in lieu of Acusensor)
 _____ BEA IXIO-DT1 (in lieu of Acusensor)
 _____ Acusensor spacer Part # V-00742
 _____ Medium Stile on H60
 _____ Fail Safe Electric Lock
 _____ Fail Secure Electric Lock
 _____ Adams Rite G86 Panic Bar (H105 only)
 _____ Key Switches in lieu of Rocker Switch
 _____ Additional Holding Beams
 _____ Qty _____
 _____ Rocker switches at location OTHER than
 _____ on interior jamb face
 _____ (include diagram with order)
 _____ Aluminum Cart Bar P/N 14-11035
 _____ Key Cylinder operated flush bolts
 _____ (H60 only)
 _____ 4550 Dead Bolt Lever/s

Finish:

_____ Clear (204)
 _____ Dk bronze (313)
 _____ Special anodize _____
 _____ Paint/Clad _____
 _____ Prep for paint by distributor

Door/Panel Glass Thickness

_____ 1/2"	Impact	H60
_____ 5/16"	Non-Impact	
_____ 7/16"	Impact	H105
_____ 1/4"	Non-Impact	