

Nabco Entrances - GT 1175 Hurricane Models H60 or H105 Shop Drawing Request

Rev. 2019

Order _____ Quote _____ Page: _____ of _____
Company: _____ Distributor #: _____ Door #: _____
Date: _____ Job Name: _____
PO #: _____ Contact: _____
Drop Ship to: _____
Ship Method: _____ Date to Ship: _____

Notes: _____

_____ **H105** _____ **Impact**
_____ **H60** _____ **Non-Impact**

Type of Unit:

_____ Quantity _____ Fixed Sidelite
_____ Bi-part _____ Full Open
_____ Single

Muntin Bars:

_____ 4" (H105 only)

Hand of Unit:

_____ Right hand *viewed from exterior*
_____ Left hand *panic breakaway direction*

Bottom Rail:

_____ 4" _____
_____ 6.5" _____
_____ 10" _____
_____ 6.5" _____
_____ 10" _____

Frame Size:

_____ Width ((H60 max. 16' / H105 max. 18'))
_____ Header Height less transom (see below)
_____ **H60** max. 7' 7-1/2" **H105** max. 8' 8"
_____ Clear Door Opening Width

Note:

All hurricane units are equipped with 1/2" jamb to jamb thresholds.

Additions/Changes:

_____ Acuzone (in lieu of Acusensor)
_____ Optex i-One (in lieu of Acusensor)
_____ BEA IXIO-DT1 (in lieu of Acusensor)
_____ Acusensor spacer Part # V-00742
_____ Medium Stile on H60
_____ Fail Safe Electric Lock
_____ Fail Secure Electric Lock
_____ Adams Rite G86 Panic Bar (H105 only)
_____ Key Switches in lieu of Rocker Switch
_____ Additional Holding Beams
_____ Qty _____
_____ Rocker switches at location OTHER than
_____ on interior jamb face
_____ (include diagram with order)
_____ Aluminum Cart Bar P/N 14-11035
_____ Key Cylinder operated flush bolts
_____ (H60 only)
_____ 4550 Dead Bolt Lever/s

Finish:

_____ Clear (204)
_____ Dk bronze (313)
_____ Special anodize _____
_____ Paint/Clad _____
_____ Prep for paint by distributor

Door/Panel Glass Thickness

_____ 1/2" Impact _____ H60
_____ 5/16" Non-Impact _____
_____ 7/16" Impact _____ H105
_____ 1/4" Non-Impact _____