

# Nabco Entrances - GT1400 Fold Door - ORDER FORM

Rev. 2019

Quote: \_\_\_\_\_ Page: \_\_\_\_\_ of \_\_\_\_\_  
 Company: \_\_\_\_\_ Distributor #: \_\_\_\_\_ Door #: \_\_\_\_\_  
 Date: \_\_\_\_\_ Job Name: \_\_\_\_\_  
 PO #: \_\_\_\_\_ Contact: \_\_\_\_\_  
 Drop Ship to: \_\_\_\_\_  
 Ship Method: \_\_\_\_\_ Date to Ship: \_\_\_\_\_

**Notes:**

  
  
  
  

**Type of Unit:**  
 \_\_\_\_\_ Quantity  
 \_\_\_\_\_ Single Fold *GT1400 folds and breaks*  
 \_\_\_\_\_ Bi-Fold *open in the same direction*

**Hand of Unit:**  
 \_\_\_\_\_ Right hand (door slides to the right when viewed from interior)  
 \_\_\_\_\_ Left hand (door slides to the *left* when viewed from interior)

**Frame Size:**  
 \_\_\_\_\_ Width  
 \_\_\_\_\_ Header Height (std. = 91-1/2")  
 \_\_\_\_\_ Height Including Transom  
 \_\_\_\_\_ Number of Verticals in Transom  
 \_\_\_\_\_ Clear Door Opening Width

	<u>Frame Width</u>	<u>Min</u>	<u>Max</u>
_____ Bi-Fold	6' 4"	6' 4"	9' 0"
_____ Single Fold	3' 10"	3' 10"	5' 3"

<b>Door/Panel Glass Thickness</b>	<b>Transom Glass Thickness</b>
_____ 1/4" (std.)	_____ 1/4" (std.)
_____ 1/2"	_____ 1/2"
_____ 9/16"	_____ 9/16"
_____ 5/8"	_____ 5/8"
_____ 3/4"	_____ 3/4"
_____ 7/8"	_____ 7/8"
_____ 1"	_____ 1"
_____ Hurricane	

**Finish:**  
 \_\_\_\_\_ Clear (204)  
 \_\_\_\_\_ Dk bronze (313)  
 \_\_\_\_\_ Special anodize \_\_\_\_\_  
 \_\_\_\_\_ Paint/Clad \_\_\_\_\_  
 \_\_\_\_\_ Prep for paint by distributor

**Guide Rails:**  
 \_\_\_\_\_ (Qty.) Fold Side (matches finish of door)

Length: \_\_\_\_\_ One Way Traffic (per ANSI 156.10)  
 Length: \_\_\_\_\_ Two Way Traffic (per ANSI 156.10)  
 Length: \_\_\_\_\_ Other (as specified)

**GT1400 - \_\_\_\_\_ drawing #: \_\_\_\_\_**

**Jamb Tubes:**  
 \_\_\_\_\_ Standard  
 \_\_\_\_\_ 1-3/4" x 6-3/8"  
 \_\_\_\_\_ 2" x 7"  
 \_\_\_\_\_ No Jambes Required

**Muntin Bars:**  
 \_\_\_\_\_ 2" std.  
 \_\_\_\_\_ 4"  
 \_\_\_\_\_ 4-1/2"  
 \_\_\_\_\_ 6-3/8"  
 \_\_\_\_\_ No muntins required  
 \_\_\_\_\_ Special \_\_\_\_\_  
 \_\_\_\_\_ Standard Height 42-7/8" F.F. - top  
 \_\_\_\_\_ Special location - F.F. - top  
 \_\_\_\_\_ Additional Muntin - F.F. - top

**Bottom Rail:**  
 \_\_\_\_\_ Standard  
 \_\_\_\_\_ 10"  
 \_\_\_\_\_ Other \_\_\_\_\_

**Additional Sensors:**  
 Header Mounted Sensors:  
 \_\_\_\_\_ (Qty.) Acusensor M  
 \_\_\_\_\_ (Qty.) Optex i-One  
 \_\_\_\_\_ (Qty.) Optex Reaction2

**Locks:**  
 \_\_\_\_\_ Manual - manual lock(s) with thumb turn and key cylinder (standard)  
 \_\_\_\_\_ Flush Bolt - lock(s) at fold point(s)  
 \_\_\_\_\_ No Cylinder or Flush Bolts  
 \_\_\_\_\_ Electro-Magnetic Lock (fail-safe)

**Extras:**  
 \_\_\_\_\_ Threshold  
 \_\_\_\_\_ Rocker switches at location OTHER than on interior jamb face (include diagram with order)