

Nabco Entrances - GT1400 Fold Door - Shop Drawing Request

Rev. 2019

Quote: _____ Page: _____ of _____
 Company: _____ Distributor #: _____ Door #: _____
 Date: _____ Job Name: _____
 PO #: _____ Contact: _____
 Drop Ship to: _____
 Ship Method: _____ Date to Ship: _____

Notes:

Type of Unit:

_____ Quantity
 _____ Single Fold *GT1400 folds and breaks*
 _____ Bi-Fold *open in the same direction*

Hand of Unit:

_____ Right hand (door slides to the right when viewed from interior)
 _____ Left hand (door slides to the *left* when viewed from interior)

Frame Size:

_____ Width
 _____ Header Height (std. = 91-1/2")
 _____ Height Including Transom
 _____ Number of Verticals in Transom
 _____ Clear Door Opening Width

	<u>Frame Width</u>	<u>Min</u>	<u>Max</u>
_____ Bi-Fold	6' 4"	6' 4"	9' 0"
_____ Single Fold	3' 10"	3' 10"	5' 3"

Door/Panel Glass Thickness

_____ 1/4" (std.)
 _____ 1/2"
 _____ 9/16"
 _____ 5/8"
 _____ 3/4"
 _____ 7/8"
 _____ 1"
 _____ Hurricane

Transom Glass Thickness

_____ 1/4" (std.)
 _____ 1/2"
 _____ 9/16"
 _____ 5/8"
 _____ 3/4"
 _____ 7/8"
 _____ 1"

Finish:

_____ Clear (204)
 _____ Dk bronze (313)
 _____ Special anodize _____
 _____ Paint/Clad _____
 _____ Prep for paint by distributor

Guide Rails:

_____ (Qty.) Fold Side (matches finish of door)

Length: _____ One Way Traffic (per ANSI 156.10)
 Length: _____ Two Way Traffic (per ANSI 156.10)
 Length: _____ Other (as specified)

GT1400 - _____ drawing #: _____

Jamb Tubes:

_____ Standard
 _____ 1-3/4" x 6-3/8"
 _____ 2" x 7"
 _____ No Jambes Required

Muntin Bars:

_____ 2" std.
 _____ 4"
 _____ 4-1/2"
 _____ 6-3/8"
 _____ No muntins required
 _____ Special _____
 _____ Standard Height 42-7/8" F.F. - top
 _____ Special location - F.F. - top
 _____ Additional Muntin - F.F. - top

Bottom Rail:

_____ Standard
 _____ 10"
 _____ Other _____

Additional Sensors:

Header Mounted Sensors:
 _____ (Qty.) Acusensor M
 _____ (Qty.) Optex i-One
 _____ (Qty.) Optex Reaction2

Locks:

_____ Manual - manual lock(s) with thumb turn and key cylinder (standard)
 _____ Flush Bolt - lock(s) at fold point(s)
 _____ No Cylinder or Flush Bolts
 _____ Electro-Magnetic Lock (fail-safe)

Extras:

_____ Threshold
 _____ Rocker switches at location OTHER than on interior jamb face (include diagram with order)