

# Nabco Entrances - Manual/ICU Door - Order Form

Rev. 2019

Quote: \_\_\_\_\_ Page: \_\_\_\_\_ of \_\_\_\_\_  
 Company: \_\_\_\_\_ Distributor #: \_\_\_\_\_ Door #: \_\_\_\_\_  
 Date: \_\_\_\_\_ Job Name: \_\_\_\_\_  
 PO #: \_\_\_\_\_ Contact: \_\_\_\_\_  
 Drop Ship to: \_\_\_\_\_  
 Ship Method: \_\_\_\_\_ Date to Ship: \_\_\_\_\_

ENTER "X" TO INDICATE A SELECTION

Notes:

**Type of Unit:**

\_\_\_\_\_ Quantity

**Model:**

_____ GT2100R	_____ GT2125R	_____ GT2150R
_____ GT2100L	_____ GT2125L	_____ GT2150L
_____ GT2100TR	_____ GT2125TR	_____ GT2150TR
_____ GT2100TL	_____ GT2125TL	_____ GT2150TL
_____ GT2100B	_____ GT2125B	_____ GT2150B
_____ GT2100TB	_____ GT2125TB	_____ GT2150TB

**Frame Size:**

\_\_\_\_\_ Width  
 \_\_\_\_\_ Header Height (slider std. = 88")  
 \_\_\_\_\_ Height Including Transom  
 \_\_\_\_\_ Number of Verticals in Transom  
 \_\_\_\_\_ Clear Door Opening Width

**Door/Panel Glass Thickness**

\_\_\_\_\_ 1/4" (std.)  
 \_\_\_\_\_ 1/2"  
 \_\_\_\_\_ 9/16"  
 \_\_\_\_\_ 5/8"  
 \_\_\_\_\_ 3/4"  
 \_\_\_\_\_ 7/8"  
 \_\_\_\_\_ 1"

**Transom Glass Thickness**

\_\_\_\_\_ 1/4" (std.)  
 \_\_\_\_\_ 1/2"  
 \_\_\_\_\_ 9/16"  
 \_\_\_\_\_ 5/8"  
 \_\_\_\_\_ 3/4"  
 \_\_\_\_\_ 7/8"  
 \_\_\_\_\_ 1"

**Finish:**

\_\_\_\_\_ Dk bronze (313) \_\_\_\_\_ Clear (204)  
 \_\_\_\_\_ Prep for paint by distributor  
 \_\_\_\_\_ Special anodize  
 \_\_\_\_\_ Paint/Clad

**Threshold: (applies to 2150 only)**

\_\_\_\_\_ Through Door Opening \_\_\_\_\_ Under Jambs  
 \_\_\_\_\_ Between Jambs \_\_\_\_\_ Other

**Bottom Rail:**

\_\_\_\_\_ Standard  
 \_\_\_\_\_ 6-1/2"  
 \_\_\_\_\_ 10"

Note: Air infiltration/smoke infiltration sealing automatically includes 4570 Latching System

**Jamb Tubes:**

\_\_\_\_\_ Standard  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Without Pockets  
 \_\_\_\_\_ 1-3/4" x 6-3/8"  
 \_\_\_\_\_ 2" x 5"  
 \_\_\_\_\_ 2" x 7"  
 \_\_\_\_\_ No Jambs Required

**Muntin Bars:**

\_\_\_\_\_ 2" std.  
 \_\_\_\_\_ 4"  
 \_\_\_\_\_ 6-3/8"  
 \_\_\_\_\_ 8"  
 \_\_\_\_\_ No muntins required  
 \_\_\_\_\_ Standard Height 42-1/4" F.F. - top  
 \_\_\_\_\_ Special location - F.F. - top  
 \_\_\_\_\_ Additional Muntin - F.F. - top

**Options:**

(Standard pulls are the "D" and recessed pulls)  
 \_\_\_\_\_ Recessed Handles (both sides)  
 \_\_\_\_\_ 4570 (Levers Down - Positive Latch)  
 \_\_\_\_\_ Handle + Recessed Pull  
 \_\_\_\_\_ Handle on Both Sides  
 \_\_\_\_\_ (reduces door opening on 2100 only)  
 \_\_\_\_\_ 4189 ICU Flush Lockset  
 \_\_\_\_\_ 4550 Dead Bolt Lever with Exit Indicator  
 \_\_\_\_\_ Medium Stile  
 \_\_\_\_\_ No Panic Breakout  
 \_\_\_\_\_ Delete Sidelites for Surface Applied  
 \_\_\_\_\_ Floor Sweeps  
 \_\_\_\_\_ Pile + Brush Weather Stripping  
 \_\_\_\_\_ Composite panels in bottom of doors  
 \_\_\_\_\_ Self Closing  
 \_\_\_\_\_ Hold Open  
 \_\_\_\_\_ Air infiltration/smoke sealing