Nabco	<b>Entrances - Man</b>	ual/ICU Doo	r - Shop Dr	awing Reque	est Rev. 2019	
Quote:				Page:	of	
Company:			I	Distributor #:		
Date:			Job Name:			
PO #:			Contact:			
Drop Ship	to:					
Ship Metho			Da	te to Ship:		
Only Weak						
		ENTER "X" T	O INDICATE A SI	ELECTION		
Notes:						
Type of Unit:  Quantity				Jamb Tubes: Standard		
	_ Quantity				4-1/2" Without Pockets	
Model:	CT2400D	CT2425D	OT2450D	1-3/4" x	c 6-3/8"	
	GT2100R GT2100L	GT2125R GT2125L	GT2150R GT2150L	2" x 5" 2" x 7"		
	GT2100TR	GT2125TR	GT2150TR		ibs Required	
	GT2100TL	GT2125TL	GT2150TL		•	
	GT2100B	GT2125B	GT2150B			
	GT2100TB	GT2125TB	GT2150TB	Muntin Bars: 2" std.		
Frame Size	:			2 std.		
Width Header Height (slider std. = 88") Height Including Transom				6-3/8"	8"	
				No muntins required		
	Number of Verticals in Trar Clear Door Opening Width	nsom		Standa	rd Height 42-1/4" F.F top	
	- Clear Door Opening Width				location - F.F top	
Door/Panel Glass Thickness Transom Glass Thickness				nal Muntin - F.F top		
	_1/4" (std.)	1/4" (st	d.)			
	_1/2"	1/2"		Options:		
	_9/16" _5/8"	9/16" 5/8"		(Ctandard nulla ara	the "D" and recessed nulls)	
	3/4"	3/4"		(Standard pulls are the "D" and recessed pulls)  Recessed Handles (both sides)		
	7/8"	7/8"			evers Down - Positive Latch)	
	1"	1"			Handle + Recessed Pull	
	_	<del></del>			Handle on Both Sides	
Finish:	Dis harana (242)	Class //	204)	,	s door opening on 2100 only) CU Flush Lockset	
	Dk bronze (313) Prep for paint by distributor	Clear (2	204)		ead Bolt Lever with Exit Indicator	
	Special anodize			Medium		
	Paint/Clad				ic Breakout	
	=				Sidelites for Surface Applied	
Threshold:	(-1-1			Floor S	•	
	Through Door Opening Between Jambs	Under Jambs Other		Pile + Brush Weather Stripping Composite panels in bottom of doors		
	Detween Janns	Other		Self Clo		
Bottom Rai	il:			Hold O	•	
	Standard				ration/smoke sealing	
	6-1/2"					
	10" Note: Air infil	tration/smoke infiltrat	ion sealing autom	atically includes 4570	Latching System	