

# Nabco Entrances - Single Slide Door - Shop Drawing Request

Rev. 2019

Quote: \_\_\_\_\_ Page: \_\_\_\_\_ of \_\_\_\_\_  
 Company: \_\_\_\_\_ Distributor #: \_\_\_\_\_ Door #: \_\_\_\_\_  
 Date: \_\_\_\_\_ Job Name: \_\_\_\_\_  
 PO #: \_\_\_\_\_ Contact: \_\_\_\_\_  
 Drop Ship to: \_\_\_\_\_  
 Ship Method: \_\_\_\_\_ Date to Ship: \_\_\_\_\_

Notes:

**Type of Unit:** GT1175 - drawing # \_\_\_\_\_  
 \_\_\_\_\_ Quantity  
 N/A Bi-part \_\_\_\_\_ Fixed Sidelite  
 \_\_\_\_\_ Single \_\_\_\_\_ Full Open  
 \_\_\_\_\_ Pocketed  
 N/A Telescopic \_\_\_\_\_ to interior  
 N/A All-Glass \_\_\_\_\_ to exterior  
 \_\_\_\_\_ Surface applied (\* see note 1) \_\_\_\_\_ w/ sidelite  
 \_\_\_\_\_ no sidelite

**Jamb Tubes:** \_\_\_\_\_ None Required  
 \_\_\_\_\_ Standard ~ 1-3/4" x 4-1/2"  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Single Pocket  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Double Pocket  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Without Pockets  
 \_\_\_\_\_ 1-3/4" x 6-3/8"  
 \_\_\_\_\_ 2" x 5"  
 \_\_\_\_\_ 2" x 7"  
 \_\_\_\_\_ 4-1/2" x 4-1/2" Jamb Tubes (see below)  
 \_\_\_\_\_ except AG or Telescopic

**Custom Surface Applied Units:**  
 \_\_\_\_\_ Surface Applied to Exterior with Wall Track  
 \_\_\_\_\_ Surface Applied to Interior, Breakout Thru Opening  
 (Wall Opening required to size doors correctly)  
 \_\_\_\_\_ x \_\_\_\_\_ Wall Opening (W x H)

**Muntin Bars:**  
 \_\_\_\_\_ 2" std. \_\_\_\_\_ 4"  
 \_\_\_\_\_ 8" \_\_\_\_\_ 6-3/8"  
 \_\_\_\_\_ No muntins required  
 \_\_\_\_\_ Special \_\_\_\_\_  
 \_\_\_\_\_ Standard Height 42-1/4" F.F. - top  
 \_\_\_\_\_ Special location - F.F. - top  
 \_\_\_\_\_ Additional Muntin - F.F. - top  
 \_\_\_\_\_ 6-3/8" Muntin Std. - Recessed Panic

**Hand of Unit:**  
 \_\_\_\_\_ Right hand *viewed from*  
 \_\_\_\_\_ Left hand *panic breakaway side*

**Frame Size:**  
 \_\_\_\_\_ Width \_\_\_\_\_ Header Height (std. = 91-1/2")  
 \_\_\_\_\_ Height Including Transom  
 \_\_\_\_\_ Number of Verticals in Transom  
 \_\_\_\_\_ Clear Door Opening Width

**Additions/Changes:**  
 \_\_\_\_\_ Acuzone (in lieu of Acusensor M)  
 \_\_\_\_\_ Optex i-One (in lieu of Acusensor M)  
 \_\_\_\_\_ BEA IXIO-DT1 (in lieu of Acusensor M)  
 \_\_\_\_\_ Angled spacer for Acusensor M  
 \_\_\_\_\_ Medium Stile (4")  
 \_\_\_\_\_ Fail Safe Electric Lock  
 \_\_\_\_\_ Fail Secure Electric Lock  
 \_\_\_\_\_ Fail Safe Electro-Magnetic Lock  
 \_\_\_\_\_ Surface applied push bar exit hardware  
 \_\_\_\_\_ Recessed push bar exit hardware  
 \_\_\_\_\_ Paddle exit hardware (Fixed Sidelite)  
 \_\_\_\_\_ Key Switches in lieu of Rocker Switch  
 \_\_\_\_\_ Additional Holding Beams - Qty: \_\_\_\_\_  
 \_\_\_\_\_ Access cover on opposite side of header  
 \_\_\_\_\_ Nose Caster  
 N/A Rail Locks for All Glass Sliders  
 N/A Include Weathering for All Glass  
 \_\_\_\_\_ Prep as Clean Room unit  
 (except Telescopic or All Glass)  
 \_\_\_\_\_ Rocker switches at location OTHER  
 than on interior jamb face  
 (include diagram with order)  
 \_\_\_\_\_ Aluminum Cart Bars Pt # 14-11035  
 (except All Glass)  
 (specify which panels to receive bars)  
 \_\_\_\_\_ Additional sidelite/s  
 \_\_\_\_\_ Width  
 \_\_\_\_\_ Height  
 \_\_\_\_\_ Muntins  
 \_\_\_\_\_ Door Closers  
 (in lieu of limit arm in doors or sidelites)

Door/Panel Glass Thickness	Transom Glass Thickness
_____ 1/4" (std.)	_____ 1/4" (std.)
_____ 1/2"	_____ 1/2"
_____ 9/16"	_____ 9/16"
_____ 5/8"	_____ 5/8"
_____ 3/4"	_____ 3/4"
_____ 7/8"	_____ 7/8"
_____ 1"	_____ 1"

**Finish:**  
 \_\_\_\_\_ Clear (204) \_\_\_\_\_ Dk bronze (313)  
 \_\_\_\_\_ Special anodize \_\_\_\_\_  
 \_\_\_\_\_ Paint/Clad \_\_\_\_\_  
 \_\_\_\_\_ Prep for paint by distributor

**Threshold:**  
 \_\_\_\_\_ 1/2" Standard \_\_\_\_\_ 1/4" Optional  
 \_\_\_\_\_ Through Door Opening  
 \_\_\_\_\_ Under Jamb's \*  
 \* Does the Total Frame Height entered in Frame Size  
 category above include height of threshold ?  
 \_\_\_\_\_ Yes \_\_\_\_\_ No  
 \_\_\_\_\_ Between Jamb's \_\_\_\_\_ Other

**Bottom Rail:**  
 \_\_\_\_\_ Standard \_\_\_\_\_ 10" \_\_\_\_\_ Other

**Note 1:** On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form. Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. The hook on the cover is ripped off on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on.