

Quote: _____ Page: _____ of _____
 Company: _____ Distributor #: _____ Door #: _____
 Date: _____ Job Name: _____
 PO #: _____ Contact: _____
 Drop Ship to: _____
 Ship Method: _____ Date to Ship: _____

Notes:

Type of Unit: **GT1175 - drawing #** _____

_____ Quantity

_____ Bi-part _____ Fixed Sidelite

_____ Single _____ Full Open

_____ N/A _____ Pocketed

_____ Telescopic

_____ All-Glass (FSL Only)

_____ Surface applied (* **see note 1**) { _____ to interior

_____ { _____ to exterior

_____ { _____ w/ sidelite

_____ { _____ no sidelite

Custom Surface Applied Units:

_____ Surface Applied to Exterior with Wall Track

_____ Surface Applied to Interior, Breakout Thru Opening

(Wall Opening required to size doors correctly)

x Wall Opening (W x H)

Hand of Unit:
 _____ Right hand *viewed from*
 _____ Left hand *panic breakaway side*

Frame Size:

_____ Width _____ Header Height (std. = 91-1/2")

_____ Total Frame Height Including Transom *

_____ Number of Verticals in Transom

_____ Clear Door Opening Width

Door/Panel Glass Thickness	Transom Glass Thickness
_____ 1/4" (std.)	_____ 1/4" (std.)
_____ 1/2"	_____ 1/2"
_____ 9/16"	_____ 9/16"
_____ 5/8"	_____ 5/8"
_____ 3/4"	_____ 3/4"
_____ 7/8"	_____ 7/8"
_____ 1"	_____ 1"

Finish:

_____ Clear (204)	_____ Dk bronze (313)
_____ Special anodize	_____
_____ Paint/Clad	_____
_____ Prep for paint by distributor	

Threshold: (* see note 2)

_____ 1/2" Standard	_____ 1/4" Optional
_____ Through Door Opening	
_____ Under Jamb's *	

* Does the Total Frame Height entered in Frame Size category above include height of threshold ?

_____ Yes < or >	_____ No
_____ Between Jamb's	_____ Other

Bottom Rail:

Standard	10"	Other
----------	-----	-------

Jamb Tubes:		None Required
N/A	Standard ~ 1-3/4" x 4-1/2"	
N/A	1-3/4" x 4-1/2" Single Pocket	
N/A	1-3/4" x 4-1/2" Double Pocket	
N/A	1-3/4" x 4-1/2" Without Pockets	
N/A	1-3/4" x 6-3/8"	
N/A	2" x 5"	
	2" x 7"	
N/A	4-1/2" x 4-1/2" Jamb Tubes (<i>see below</i>) except AG or Telescopic	

Muntin Bars:

_____ 2" std.	_____ 4"
_____ 8"	_____ 6-3/8"
_____ No muntins required	
_____ Special _____	
_____ Standard Height 42-1/4" F.F. - top	
_____ Special location - F.F. - top	
_____ Additional Muntin - F.F. - top	
_____ 6-3/8" Muntin Std. - Recessed Panic	

Additions/Changes:	
	Acuzone (in lieu of Acusensor M)
	Optex i-One (in lieu of Acusensor M)
	BEA IXIO-DT1 (in lieu of Acusensor M)
	Angled spacer for Acusensor M
	Medium Stile (4")
	Fail Safe Electric Lock
	Fail Secure Electric Lock
N/A	Fail Safe Electro-Magnetic Lock
	Surface applied push bar exit hardware
	Recessed push bar exit hardware
	Paddle exit hardware (Fixed Sidelite)
	Key Switches in lieu of Rocker Switch
	Additional Holding Beams
	Qty
N/A	Access cover on opposite side of header
N/A	Rail Locks for All Glass Sliders
N/A	Include Weathering for All Glass
N/A	Prep as Clean Room unit
	(except Telescopic or All Glass)
	Rocker switches at location OTHER
	than on interior jamb face
	(include diagram with order)
	Aluminum Cart Bars
	(except All Glass)
	(specify which panels to receive bars)
	Additional sidelite/s
	Width
	Height
	Muntins
	Door Closers
	(in lieu of limit arm in doors or sidelites)

Note 1:

Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. We rip the hook off the cover on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on. If you would like to change the location of the control switches, indicate the desired location in the Notes section above.

Note 2:

On Telescopes, a threshold jamb to jamb is necessary on a full open unit. Any threshold option is available for fixed units.