

Nabco Entrances - Bi-part Slide Door - ORDER FORM

N5

Rev. 2019

Quote: _____ Page: _____ of _____
 Company: _____ Distributor #: _____ Door #: _____
 Date: _____ Job Name: _____
 PO #: _____ Contact: _____
 Drop Ship to: _____
 Ship Method: _____ Date to Ship: _____

Notes:

Type of Unit: GT1175 - drawing # _____

_____ Quantity

_____ Bi-part _____ Fixed Sidelite

_____ Single _____ Full Open

_____ _____ Pocketed

_____ Telescopic

_____ All-Glass (FSL Only)

_____ Surface applied (* see note 1)

_____ to interior

_____ to exterior

_____ w/ sidelite

_____ no sidelite

Custom Surface Applied Units:

_____ Surface Applied to Exterior with Wall Track

_____ Surface Applied to Interior, Breakout Thru Opening

(Wall Opening required to size doors correctly)

_____ x _____ Wall Opening (W x H)

Hand of Unit:_____ Right hand *viewed from*_____ Left hand *panic breakaway side***Frame Size:**

_____ Width _____ Header Height (std. = 91-1/2")

_____ Total Frame Height Including Transom *

_____ Number of Verticals in Transom

_____ Clear Door Opening Width

Door/Panel Glass Thickness

_____ 1/4" (std.)

_____ 1/2"

_____ 9/16"

_____ 5/8"

_____ 3/4"

_____ 7/8"

_____ 1"

Transom Glass Thickness

_____ 1/4" (std.)

_____ 1/2"

_____ 9/16"

_____ 5/8"

_____ 3/4"

_____ 7/8"

_____ 1"

Finish:

_____ Clear (204)

_____ Special anodize

_____ Paint/Clad

_____ Prep for paint by distributor

_____ Dk bronze (313)

Threshold:

_____ 1/2" Standard _____ 1/4" Optional

_____ Through Door Opening

_____ Under Jambs *

* Does the Total Frame Height entered in Frame Size category above include height of threshold ?

_____ Yes < or > _____ No

_____ Between Jambs _____ Other

Bottom Rail:

_____ Standard _____ 10" _____ Other

Jamb Tubes: _____ None Required

_____ Standard ~ 1-3/4" x 4-1/2"

_____ 1-3/4" x 4-1/2" Single Pocket

_____ 1-3/4" x 4-1/2" Double Pocket

_____ 1-3/4" x 4-1/2" Without Pockets

_____ 1-3/4" x 6-3/8"

_____ 2" x 5"

_____ 2" x 7"

_____ 4-1/2" x 4-1/2" Jamb Tubes (see below)

except AG or Telescopic

Muntin Bars:

_____ 2" std. _____ 4"

_____ 8" _____ 6-3/8"

_____ No muntins required

_____ Special _____

_____ Standard Height 42-1/4" F.F. - top

_____ Special location - F.F. - top

_____ Additional Muntin - F.F. - top

_____ 6-3/8" Muntin Std. - Recessed Panic

Additions/Changes:

_____ Acuzone (in lieu of Acusensor M)

_____ Optex i-One (in lieu of Acusensor M)

_____ BEA IXIO-DT1 (in lieu of Acusensor M)

_____ Angled spacer for Acusensor M

_____ Medium Stile (4")

_____ Fail Safe Electric Lock

_____ Fail Secure Electric Lock

_____ Surface applied push bar exit hardware

_____ Recessed push bar exit hardware

_____ Paddle exit hardware (Fixed Sidelite)

_____ Key Switches in lieu of Rocker Switch

_____ Additional Holding Beams

_____ Qty

_____ Access cover on opposite side of header

_____ N/A Rail Locks for All Glass Sliders

_____ N/A Include Weathering for All Glass

_____ Prep as Clean Room unit

(except Telescopic or All Glass)

_____ Rocker switches at location OTHER

than on interior jamb face

(include diagram with order)

_____ Aluminum Cart Bars

(except All Glass)

(specify which panels to receive bars)

_____ Additional sidelite/s

_____ Width

_____ Height

_____ Muntins

_____ Door Closers

(in lieu of limit arm in doors or sidelites)

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form.