

**Nabco Entrances - Bi-part Slide Door - Shop Drawing Request**

N5 Rev. 2019

Quote: \_\_\_\_\_ Page: \_\_\_\_\_ of \_\_\_\_\_  
 Company: \_\_\_\_\_ Distributor #: \_\_\_\_\_ Door #: \_\_\_\_\_  
 Date: \_\_\_\_\_ Job Name: \_\_\_\_\_  
 PO #: \_\_\_\_\_ Contact: \_\_\_\_\_  
 Drop Ship to: \_\_\_\_\_  
 Ship Method: \_\_\_\_\_ Date to Ship: \_\_\_\_\_

Notes:

**Type of Unit:** **GT1175 - drawing #** \_\_\_\_\_  
 \_\_\_\_\_ Quantity  
 \_\_\_\_\_ Bi-part \_\_\_\_\_ Fixed Sidelite  
 \_\_\_\_\_ Single \_\_\_\_\_ Full Open  
 \_\_\_\_\_ \_\_\_\_\_ Pocketed  
 \_\_\_\_\_ Telescopic  
 \_\_\_\_\_ All-Glass (FSL Only)  
 \_\_\_\_\_ Surface applied (\* see note 1) { \_\_\_\_\_ to interior  
 \_\_\_\_\_ to exterior  
 \_\_\_\_\_ w/ sidelite  
 \_\_\_\_\_ no sidelite

**Custom Surface Applied Units:**  
 \_\_\_\_\_ Surface Applied to Exterior with Wall Track  
 \_\_\_\_\_ Surface Applied to Interior, Breakout Thru Opening  
 (Wall Opening required to size doors correctly)  
 \_\_\_\_\_ x \_\_\_\_\_ Wall Opening (W x H)

**Jamb Tubes:** \_\_\_\_\_ None Required  
 \_\_\_\_\_ Standard ~ 1-3/4" x 4-1/2"  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Single Pocket  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Double Pocket  
 \_\_\_\_\_ 1-3/4" x 4-1/2" Without Pockets  
 \_\_\_\_\_ 1-3/4" x 6-3/8"  
 \_\_\_\_\_ 2" x 5"  
 \_\_\_\_\_ 2" x 7"  
 \_\_\_\_\_ 4-1/2" x 4-1/2" Jamb Tubes (see below)  
 except AG or Telescopic

**Muntin Bars:**  
 \_\_\_\_\_ 2" std. \_\_\_\_\_ 4"  
 \_\_\_\_\_ 8" \_\_\_\_\_ 6-3/8"  
 \_\_\_\_\_ No muntins required  
 \_\_\_\_\_ Special \_\_\_\_\_  
 \_\_\_\_\_ Standard Height 42-1/4" F.F. - top  
 \_\_\_\_\_ Special location - F.F. - top  
 \_\_\_\_\_ Additional Muntin - F.F. - top  
 \_\_\_\_\_ 6-3/8" Muntin Std. - Recessed Panic

**Hand of Unit:**  
 \_\_\_\_\_ Right hand *viewed from*  
 \_\_\_\_\_ Left hand *panic breakaway side*

**Frame Size:**  
 \_\_\_\_\_ Width \_\_\_\_\_ Header Height (std. = 91-1/2")  
 \_\_\_\_\_ Total Frame Height Including Transom  
 \_\_\_\_\_ Number of Verticals in Transom  
 \_\_\_\_\_ Clear Door Opening Width

**Additions/Changes:**  
 \_\_\_\_\_ Acuzone (in lieu of Acusensor M)  
 \_\_\_\_\_ Optex i-One (in lieu of Acusensor M)  
 \_\_\_\_\_ BEA IXIO-DT1 (in lieu of Acusensor M)  
 \_\_\_\_\_ Angled spacer for Acusensor M  
 \_\_\_\_\_ Medium Stile (4")  
 \_\_\_\_\_ Fail Safe Electric Lock  
 \_\_\_\_\_ Fail Secure Electric Lock  
 \_\_\_\_\_ Surface applied push bar exit hardware  
 \_\_\_\_\_ Recessed push bar exit hardware  
 \_\_\_\_\_ Paddle exit hardware (Fixed Sidelite)  
 \_\_\_\_\_ Key Switches in lieu of Rocker Switch  
 \_\_\_\_\_ Additional Holding Beams  
 \_\_\_\_\_ Qty \_\_\_\_\_  
 \_\_\_\_\_ Access cover on opposite side of header  
 \_\_\_\_\_ N/A Rail Locks for All Glass Sliders  
 \_\_\_\_\_ N/A Include Weathering for All Glass  
 \_\_\_\_\_ Prep as Clean Room unit  
 (except Telescopic or All Glass)  
 \_\_\_\_\_ Rocker switches at location OTHER  
 than on interior jamb face  
 (include diagram with order)  
 \_\_\_\_\_ Aluminum Cart Bars  
 (except All Glass)  
 (specify which panels to receive bars)  
 \_\_\_\_\_ Additional sidelite/s  
 \_\_\_\_\_ Width \_\_\_\_\_  
 \_\_\_\_\_ Height \_\_\_\_\_  
 \_\_\_\_\_ Muntins \_\_\_\_\_  
 \_\_\_\_\_ Door Closers  
 (in lieu of limit arm in doors or sidelites)

<b>Door/Panel Glass Thickness</b>	<b>Transom Glass Thickness</b>
_____ 1/4" (std.)	_____ 1/4" (std.)
_____ 1/2"	_____ 1/2"
_____ 9/16"	_____ 9/16"
_____ 5/8"	_____ 5/8"
_____ 3/4"	_____ 3/4"
_____ 7/8"	_____ 7/8"
_____ 1"	_____ 1"

**Finish:**  
 \_\_\_\_\_ Clear (204) \_\_\_\_\_ Dk bronze (313)  
 \_\_\_\_\_ Special anodize \_\_\_\_\_  
 \_\_\_\_\_ Paint/Clad \_\_\_\_\_  
 \_\_\_\_\_ Prep for paint by distributor \_\_\_\_\_

**Threshold:**  
 \_\_\_\_\_ 1/2" Standard \_\_\_\_\_ 1/4" Optional  
 \_\_\_\_\_ Through Door Opening  
 \_\_\_\_\_ Under Jambs \*  
 \* Does the Total Frame Height entered in Frame Size  
 category above include height of threshold ?  
 \_\_\_\_\_ Yes < or > \_\_\_\_\_ No  
 \_\_\_\_\_ Between Jambs \_\_\_\_\_ Other

**Bottom Rail:**  
 \_\_\_\_\_ Standard \_\_\_\_\_ 10" \_\_\_\_\_ Other

**Note 1:** On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form.