

NABCO Entrances - GT 1175 Hurricane Models H60 or H105 Order Form

N1

Rev. 2020

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

<input type="checkbox"/> H105	<input type="checkbox"/> Impact
<input type="checkbox"/> H60	<input type="checkbox"/> Non-Impact

Type of Unit:

<input type="checkbox"/> Quantity	<input type="checkbox"/> Fixed Sidelite
<input type="checkbox"/> Bi-part	<input type="checkbox"/> Full Open
<input type="checkbox"/> Single	

Muntin Bars:

<input type="checkbox"/> 4" (H105 only)

Hand of Unit:

<input type="checkbox"/> Right hand	<i>viewed from exterior panic breakaway direction</i>
<input type="checkbox"/> Left hand	

Bottom Rail:

<input type="checkbox"/> 4"	H60
<input type="checkbox"/> 6.5"	
<input type="checkbox"/> 10"	
<input type="checkbox"/> 6.5"	H105
<input type="checkbox"/> 10"	

Additions/Changes:

<input type="checkbox"/>	Acuzone (in lieu of Acusensor)
<input type="checkbox"/>	Optex i-One (in lieu of Acusensor)
<input type="checkbox"/>	BEA IXIO-DT1 (in lieu of Acusensor)
<input type="checkbox"/>	Acusensor spacer Part # V-00742
<input type="checkbox"/>	Medium Stile on H60
<input type="checkbox"/>	Fail Safe Electric Lock
<input type="checkbox"/>	Fail Secure Electric Lock
<input type="checkbox"/>	Adams Rite G86 Panic Bar (H105 only)
<input type="checkbox"/>	Key Switches in lieu of Rocker Switch
<input type="checkbox"/>	Additional Holding Beams
<input type="checkbox"/>	Qty
<input type="checkbox"/>	Rocker switches at location OTHER than on interior jamb face (include diagram with order)
<input type="checkbox"/>	Aluminum Cart Bar P/N 14-11035
<input type="checkbox"/>	Key Cylinder operated flush bolts (H60 only)
<input type="checkbox"/>	4550 Dead Bolt Lever/s

Finish:

<input type="checkbox"/> Clear (204)	<input type="checkbox"/> Black
<input type="checkbox"/> Dark bronze (313)	<input type="checkbox"/> Paint/Clad
<input type="checkbox"/> Prep for paint by distributor	<input type="checkbox"/> Special anodized

Frame Size:

<input type="checkbox"/>	Width ((H60 max. 16' / H105 max. 18')
<input type="checkbox"/>	Header Height less transom (see below)
<input type="checkbox"/>	H60 max. 7' 7-1/2" H105 max. 8' 8"
<input type="checkbox"/>	Clear Door Opening Width

Door/Panel Glass Thickness

<input type="checkbox"/> 1/2"	Impact	H60
<input type="checkbox"/> 5/16"	Non-Impact	
<input type="checkbox"/> 7/16"	Impact	H105
<input type="checkbox"/> 1/4"	Non-Impact	

Note:
All hurricane units are equipped with 1/2" jamb to jamb thresholds.