

NABCO Entrances - GT1400 Fold Door - ORDER FORM

15-9391-INTERACTIVE
Rev. 2020

IN 1

Quote: _____ Page: _____ of _____

Company: _____ Distributor #: _____ Door #: _____

Date: _____ Job Name: _____

PO #: _____ Contact: _____

Drop Ship to: _____

Ship Method: _____ Date to Ship: _____

Notes:

Type of Unit: _____ **GT1400 - _____ drawing #:** _____

_____ Quantity
 _____ Single Fold *GT1400 folds and breaks*
 _____ Bi-Fold *open in the same direction*

Jamb Tubes:
 _____ Standard
 _____ 1-3/4" x 6-3/8"
 _____ 2" x 7"
 _____ No Jamb Required

Hand of Unit:
 _____ Right hand (door slides to the right when viewed from interior)
 _____ Left hand (door slides to the *left* when viewed from interior)

Muntin Bars:
 _____ 2" std.
 _____ 4"
 _____ 4-1/2"
 _____ 6-3/8"
 _____ No muntins required
 _____ Special _____
 _____ Standard Height 42-7/8" F.F. - top
 _____ Special location - F.F. - top
 _____ Additional Muntin - F.F. - top

Frame Size:
 _____ Width
 _____ Header Height (std. = 91-1/2")
 _____ Height Including Transom
 _____ Number of Verticals in Transom
 _____ Clear Door Opening Width

	<u>Frame Width</u>	<u>Min</u>	<u>Max</u>
Bi-Fold	6' 4"	9' 0"	
Single Fold	3' 10"	5' 3"	

Bottom Rail:
 _____ Standard
 _____ 10"
 _____ Other _____

Door/Panel Glass Thickness	Transom Glass Thickness
_____ 1/4" (std.)	_____ 1/4" (std.)
_____ 1/2"	_____ 1/2"
_____ 9/16"	_____ 9/16"
_____ 5/8"	_____ 5/8"
_____ 3/4"	_____ 3/4"
_____ 7/8"	_____ 7/8"
_____ 1"	_____ 1"
_____ Hurricane	

Additional Sensors:
 Header Mounted Sensors:
 _____ (Qty.) Acusensor M
 _____ (Qty.) Optex i-One
 _____ (Qty.) Optex Reaction2

Finish:

_____ Dk bronze (313)	_____ Clear (204)
_____ Prep for paint by distributor	_____ Black
_____ Special anodize	_____
_____ Paint/Clad	_____

Locks:
 _____ Manual - manual lock(s) with thumb
 _____ turn and key cylinder (standard)
 _____ Flush Bolt - lock(s) at fold point(s)
 _____ No Cylinder or Flush Bolts
 _____ Electro-Magnetic Lock (fail-safe)

Guide Rails:
 _____ (Qty.) Fold Side (matches finish of door)

Length: _____ One Way Traffic (per ANSI 156.10)
 Length: _____ Two Way Traffic (per ANSI 156.10)
 Length: _____ Other (as specified)

Extras:
 _____ Threshold
 _____ Rocker switches at location OTHER
 _____ than on interior jamb face
 _____ (include diagram with order)

Refer to Product Configuration and Pricing Manual for Additional Information