NABCO	Entrances - Mar	nual/ICl	J Door -	ORDER	FORM	N1	Rev. 2020
Quote:				Page		of	
Company:		_		Distributor #	:	Door #:	
Date:			Job Name:	- :			
PO #:			Contact	:			
Drop Ship to:							
Ship Method:				Date to Ship	:		
Notes:							
Type of Uni					Jamb Tubes:		
	Quantity					Standard	
Model:					-	1-3/4" x 4-	1/2" Without Pockets
	GT2100R	GT2125R		GT2150R		1-3/4" x 6-3	3/8"
	GT2100L	GT2125L		GT2150L		2" x 5"	
	GT2100TR	GT2125TR		GT2150TR		2" x 7"	
	GT2100TL	GT2125TL		GT2150TL		No Jambs F	Required
	GT2100B	GT2125B		GT2150B	Muntin Bars:		
	GT2100TB	GT2125TB		GT2150TB		2" std.	
Frame Size	:			_		4"	
	Width					6-3/8"	
	Header Height (slider std. = 88") Height Including Transom Number of Verticals in Transom					8"	
						No munting	required
	Clear Door Opening Width					Standard H	eight 42-1/4" F.F top
Door/Pane	oor/Panel Glass Thickness Transom Glass Th			kness		Special loc	ation - F.F top
	1/4" (std.)		1/4" (std.)			 Additional	Muntin - F.F top
	1/2"		1/2"		Options:		
	9/16"		9/16"		(Standard pulls	are the "D"	and recessed pulls)
	5/8"		5/8"			Recessed H	andles (both sides)
	3/4"		3/4"		-	 4570 (Leve	rs Down - Positive Latch)
	7/8"		7/8"			_ -	Handle + Recessed Pull
			- 1"				Handle on Both Sides
Finish:	-		=			(reduces do	oor opening on 2100 only)
	Dk bronze (313)		Clear (204)			4189 ICU FI	ush Lockset
	Prep for paint by distri	butor	Black		-	 4550 Dead	Bolt Lever with Exit Indicat
	Special anodize		-			Medium Sti	le
	- Paint/Clad		•			— No Panic Bı	reakout
Threshold:	- (applies to 2150 o	nly)	•			— Delete Side	elites for Surface Applied
	Through Door Opening		Under Jamb	os		Floor Swee	ps
	Between Jambs Other					_	n Weather Stripping
Bottom Rail	_		_			_	panels in bottom of doors
	Standard					· Self Closing	•
	6-1/2"					Hold Open	
	=	iltration/sm	noke infiltrat	ion sealing	automatically in		atching System