

NABCO Entrances - All Glass Slide Door - Quote Request Form

USA	Revision
2022	2.8.N

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

Type of Unit:	GT1175 -drawing #	Jamb Tubes:	None Required
Quantity			Standard - 1-3/4" x 4-1/2"
Bi-part			1-3/4" x 4-1/2" Single Pocket
Single	N/A		1-3/4" x 4-1/2" Double Pocket
	N/A		1-3/4" x 4-1/2" Without Pockets
			1-3/4" x 4-1/2" Without Pockets
			1-3/4" x 6-3/8"
			2" x 5"
			2" x 7"
Surface applied (* see note 1)	N/A		

(Wall Opening required to size doors correctly)

x Wall Opening (W x H)

Hand of Unit:	
Right hand	viewed from
Left hand	panic breakaway side

Frame Size:	
Width	
Clear Door Opening Width	
Header Height (Std = 91-1/2")	
Transom Height from FF	
Number of Verticals in Transom	
Extended sidelite (in feet)	

Door/Panel Glass Thickness	Transom Glass Thickness
1/4" (std.)	1/4" (std.)
1/2"	1/2"
9/16"	9/16"
5/8"	5/8"
3/4"	3/4"
7/8"	7/8"
1"	1"

Threshold:	
1/2" Standard	1/4" Optional
Through Door Opening	
Under Jamb's *	

\* Does the Total Frame Height entered in Frame Size category above include height of threshold?

Yes < or >	No
Between Jamb's	Other

Additions/Changes:	
	Acuzone (in lieu of Acusensor M)
	Optex i-One (in lieu of Acusensor M)
	BEA IXIO-DT1 (in lieu of Acusensor M)
	Angled spacer for Acusensor M
	Fail Safe Electric Lock
	Fail Secure Electric Lock
	Fail Safe Electro-Magnetic Lock
	Key Switches in lieu of Rocker Switch
	Additional Holding Beams Qty
	Rail Locks for All Glass Sliders
	Include Weathering for All Glass
	Change Rocker Switches location (include diagram)
	Aluminum Cart Bars (specify panels need bars)
	Additional sidelite(s)
	Width
	Height
	Muntins

Finish:	
Clear (204)	Black
Dark bronze (313)	Paint/Clad
Prep for paint by distributor	Special anodized

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form.