

NABCO Entrances - Bi-part Slide Door - Quote Request Form

|               |  |                |  |         |          |
|---------------|--|----------------|--|---------|----------|
| Quote:        |  | Page:          |  | USA     | Revision |
| Company:      |  | Distributor #: |  | 2022    | 2.8.T    |
| Date:         |  | Job Name:      |  | of      |          |
| PO #:         |  | Contact:       |  | Door #: |          |
| Drop Ship to: |  |                |  |         |          |
| Ship Method:  |  | Date to Ship:  |  |         |          |
| Notes:        |  |                |  |         |          |

|                                                    |                                                                                                  |                                |                    |                                         |  |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------|--------------------|-----------------------------------------|--|
| Type of Unit:                                      | GT1175 - drawing #                                                                               |                                | Jamb Tubes:        | None Required                           |  |
| Quantity                                           | Fixed Sidelite                                                                                   |                                |                    | Standard ~ 1-3/4" x 4-1/2"              |  |
|                                                    | Full Open                                                                                        |                                |                    | 1-3/4" x 4-1/2" Single Pocket           |  |
| Bi-part                                            | Pocketed                                                                                         |                                |                    | 1-3/4" x 4-1/2" Double Pocket           |  |
| Surface applied (* see note 1)                     | {                                                                                                |                                |                    | 1-3/4" x 4-1/2" Without Pockets         |  |
|                                                    |                                                                                                  |                                | to interior        | 1-3/4" x 6-3/8"                         |  |
|                                                    |                                                                                                  |                                | to exterior        | 2" x 5"                                 |  |
|                                                    |                                                                                                  |                                | w/ sidelite        | 2" x 7"                                 |  |
| Custom Surface Applied Units:                      |                                                                                                  |                                |                    | 4-1/2" x 4-1/2" Jamb Tubes (see below)  |  |
| Surface Applied to Exterior with Wall Track        |                                                                                                  |                                | Muntin Bars:       | 2" std. 4"                              |  |
| Surface Applied to Interior, Breakout Thru Opening |                                                                                                  |                                |                    | 8" 6-3/8"                               |  |
| (Wall Opening required to size doors correctly)    |                                                                                                  |                                |                    | No muntins required                     |  |
|                                                    | x                                                                                                | Wall Opening (W x H)           |                    | Special                                 |  |
| Hand of Unit:                                      | Right hand                                                                                       | viewed from                    |                    | Standard Height 42-1/4" F.F. - top      |  |
|                                                    | Left hand                                                                                        | panic breakaway side           |                    | Special location - F.F. - top           |  |
| Frame Size:                                        | Width                                                                                            | Header Height (std. = 91-1/2") |                    | Additional Muntin - F.F. - top          |  |
|                                                    | Total Frame Height Including Transom                                                             |                                |                    | 6-3/8" Muntin Std. - Recessed Panic     |  |
|                                                    | Number of Verticals in Transom                                                                   |                                | Additions/Changes: |                                         |  |
|                                                    | Clear Door Opening Width                                                                         |                                |                    | Acuzone (in lieu of Acusensor M)        |  |
| Door/Panel Glass Thickness                         | Transom Glass Thickness                                                                          |                                |                    | Optex i-One (in lieu of Acusensor M)    |  |
| 1/4" (std.)                                        | 1/4" (std.)                                                                                      |                                |                    | BEA IXIO-DT1 (in lieu of Acusensor M)   |  |
| 1/2"                                               | 1/2"                                                                                             |                                |                    | Angled spacer for Acusensor M           |  |
| 9/16"                                              | 9/16"                                                                                            |                                |                    | Medium Stile (4")                       |  |
| 5/8"                                               | 5/8"                                                                                             |                                |                    | Fail Safe Electric Lock                 |  |
| 3/4"                                               | 3/4"                                                                                             |                                |                    | Fail Secure Electric Lock               |  |
| 7/8"                                               | 7/8"                                                                                             |                                |                    | Fail Safe Electro-Magnetic Lock         |  |
| 1"                                                 | 1"                                                                                               |                                |                    | Surface applied push bar exit hardware  |  |
| Finish:                                            | Clear (204)                                                                                      | Dk bronze (313)                |                    | Recessed push bar exit hardware         |  |
|                                                    | Special anodize                                                                                  |                                |                    | Paddle exit hardware (Fixed Sidelite)   |  |
|                                                    | Paint/Clad                                                                                       |                                |                    | Key Switches in lieu of Rocker Switch   |  |
|                                                    | Prep for paint by distributor                                                                    |                                |                    | Additional Holding Beams                |  |
| Threshold:                                         | 1/2" Standard                                                                                    | 1/4" Optional                  |                    | Access cover on opposite side of header |  |
|                                                    | Through Door Opening                                                                             |                                |                    | Prep as Clean Room unit                 |  |
|                                                    | Under Jambs *                                                                                    |                                |                    | Rocker switches at location OTHER       |  |
|                                                    | * Does the Total Frame Height entered in Frame Size category above include height of threshold ? |                                |                    | than on interior jamb face              |  |
|                                                    | Yes < or >                                                                                       | No                             |                    | (include diagram with order)            |  |
|                                                    | Between Jambs                                                                                    | Other                          |                    | Aluminum Cart Bars                      |  |
| Bottom Rail:                                       | Standard                                                                                         | 10"                            |                    | (specify which panels to receive bars)  |  |
|                                                    |                                                                                                  | Other                          |                    | Additional sidelite/s                   |  |
|                                                    |                                                                                                  |                                |                    | Width                                   |  |
|                                                    |                                                                                                  |                                |                    | Height                                  |  |
|                                                    |                                                                                                  |                                |                    | Muntins                                 |  |

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form. Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. The hook on the cover is ripped off on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on.