

NABCO Entrances - Bi-part Slide Door - ORDER FORM

Quote:		Page:		USA	Revision
Company:		Distributor #:		2022	2.8.T
Date:		Job Name:		of	
PO #:		Contact:		Door #:	
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

Type of Unit:	GT1175 - drawing #	Jamb Tubes:	None Required
Quantity	Fixed Sidelite	Standard ~ 1-3/4" x 4-1/2"	
	Full Open	1-3/4" x 4-1/2" Single Pocket	
Bi-part	Pocketed	1-3/4" x 4-1/2" Double Pocket	
Surface applied (* see note 1)	{	1-3/4" x 4-1/2" Without Pockets	
		1-3/4" x 6-3/8"	
		2" x 5"	
		2" x 7"	
Custom Surface Applied Units:		4-1/2" x 4-1/2" Jamb Tubes (see below)	
Surface Applied to Exterior with Wall Track		Muntin Bars:	
Surface Applied to Interior, Breakout Thru Opening		2" std.	4"
(Wall Opening required to size doors correctly)		8"	6-3/8"
x Wall Opening (W x H)		No muntins required	
Hand of Unit:		Special	
Right hand	viewed from	Standard Height 42-1/4" F.F. - top	
Left hand	panic breakaway side	Special location - F.F. - top	
Frame Size:		Additional Muntin - F.F. - top	
Width	Header Height (std. = 91-1/2")	6-3/8" Muntin Std. - Recessed Panic	
Total Frame Height Including Transom		Additions/Changes:	
Number of Verticals in Transom		Acuzone (in lieu of Acusensor M)	
Clear Door Opening Width		Optex i-One (in lieu of Acusensor M)	
Door/Panel Glass Thickness	Transom Glass Thickness	BEA IXIO-DT1 (in lieu of Acusensor M)	
1/4" (std.)	1/4" (std.)	Angled spacer for Acusensor M	
1/2"	1/2"	Medium Stile (4")	
9/16"	9/16"	Fail Safe Electric Lock	
5/8"	5/8"	Fail Secure Electric Lock	
3/4"	3/4"	Fail Safe Electro-Magnetic Lock	
7/8"	7/8"	Surface applied push bar exit hardware	
1"	1"	Recessed push bar exit hardware	
Finish:		Paddle exit hardware (Fixed Sidelite)	
Clear (204)	Dk bronze (313)	Key Switches in lieu of Rocker Switch	
Special anodize		Additional Holding Beams	
Paint/Clad		Access cover on opposite side of header	
Prep for paint by distributor		Prep as Clean Room unit	
Threshold:		Rocker switches at location OTHER	
1/2" Standard	1/4" Optional	than on interior jamb face	
Through Door Opening		(include diagram with order)	
Under Jambs *		Aluminum Cart Bars	
* Does the Total Frame Height entered in Frame Size		(specify which panels to receive bars)	
category above include height of threshold ?		Additional sidelite/s	
Yes < or >	No	Width	
Between Jambs	Other	Height	
Bottom Rail:		Muntins	
Standard	10"		
	Other		

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form. Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. The hook on the cover is ripped off on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on.