

NABCO- STORM Series Hurricane Doors - ORDER FORM

USA	Revision
2022	2.8.T

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

Level E	Impact
H105	Non-Impact
H60	

Type of Unit:	
Quantity	Fixed Sidelite
Bi-part	Full Open
Single	

Muntin Bars:

4" (H105 only)

Hand of Unit:	
Right hand	<i>viewed from exterior</i>
Left hand	<i>panic breakaway direction</i>

Bottom Rail:	
4"	H60
6.5"	
10"	
6.5"	H105
10"	

Frame Size:	
Width ((H60 max. 16' / H105 max. 18')	
Header Height less transom (see below)	
H60 max. 7' 7-1/2"	H105 max. 8' 8"
Clear Door Opening Width	

Note:

All hurricane units are equipped with 1/2" jamb to jamb thresholds.

Additions/Changes:

Acuzone (in lieu of Acusensor)

Optex i-One (in lieu of Acusensor)

BEA IXIO-DT1 (in lieu of Acusensor)

Acusensor spacer Part # V-00742

Medium Stile on H60

Fail Safe Electric Lock

Fail Secure Electric Lock

Adams Rite G86 Panic Bar (H105 only)

Key Switches in lieu of Rocker Switch

Additional Holding Beams

Qty

Rocker switches at location OTHER than on interior jamb face (include diagram with order)

Aluminum Cart Bar P/N 14-11035

Key Cylinder operated flush bolts (H60 only)

4550 Dead Bolt Lever/s

Finish:	
Clear (204)	Black
Dark bronze (313)	Paint/Clad
Prep for paint by distributor	Special anodized

Door/Panel Glass Thickness		
1/2"	Impact	H60
5/16"	Non-Impact	
7/16"	Impact	H105
1/4"	Non-Impact	
9/16"	Impact	Level E
	Non-Impact	