

NABCO Entrances - Single Slide Door - ORDER FORM

USA	Revision
2022	2.8.T

Quote: _____	Page: _____ of _____
Company: _____	Distributor #: _____ Door #: _____
Date: _____	Job Name: _____
PO #: _____	Contact: _____
Drop Ship to: _____	
Ship Method: _____	Date to Ship: _____

Notes: _____

Type of Unit:	GT1175 -drawing # _____	Quantity _____
NA Bi-part _____	Fixed Sidelite _____	Jamb Tubes: _____ None Required
_____ Single _____	Full Open _____	_____ Standard - 1-3/4" x 4-1/2"
_____ _____	Pocketed _____	_____ 1-3/4" x 4-1/2" Single Pocket
NA Telescopic _____	_____ to interior _____	_____ 1-3/4" x 4-1/2" Double Pocket
NA All-Glass (FSL Only) _____	_____ to exterior _____	_____ 1-3/4" x 4-1/2" Without Pockets
_____ Surface applied* ^{Note 1} _____	w/ sidelite _____	_____ 1-3/4" x 6-3/8"
	no sidelite _____	_____ 2" x 5"
Custom Surface Applied Units:		_____ 2" x 7"
_____ Surface Applied to Exterior with Wall Track		_____ 4-1/2" x 4-1/2" Jamb Tubes (see below)
_____ Surface Applied to Interior, Breakout Thru Opening		Muntin Bars:
(Wall Opening required to size doors correctly)		_____ 2" std. _____ 4"
_____ x _____ Wall Opening (W x H)		_____ 8" _____ 6-3/8"
Hand of Unit: (viewed from panic breakaway side)		_____ No muntins required
_____ Right hand _____ Left hand		_____ Special _____
		_____ Standard Height 42-1/4" F.F. - top
Frame Size:		_____ Special location - F.F. - top
_____ Width _____ Header Height		_____ Additional Muntin - F.F. - top
_____ Total Frame Height Including Transom* (std.=91-1/2")		_____ 6-3/8" Muntin Std. - Recessed Panic
_____ Number of Verticals in Transom		Additions/Changes:
_____ Clear Door Opening Width		_____ Acuzone (in lieu of Acusensor M)
Door/Panel Glass Thickness	Transom Glass Thickness	_____ Optex i-One (in lieu of Acusensor M)
_____ 1/4" (std.) _____ 1/4" (std.)	_____ 1/2" _____ 1/2"	_____ BEA IXIO-DT1 (in lieu of Acusensor M)
_____ 1/2" _____ 1/2"	_____ 9/16" _____ 9/16"	_____ Angled spacer for Acusensor M
_____ 9/16" _____ 9/16"	_____ 5/8" _____ 5/8"	_____ Medium Stile (4")
_____ 5/8" _____ 5/8"	_____ 3/4" _____ 3/4"	_____ Fail Safe Electric Lock
_____ 3/4" _____ 3/4"	_____ 7/8" _____ 7/8"	_____ Fail Secure Electric Lock
_____ 7/8" _____ 7/8"	_____ 1" _____ 1"	_____ Fail Safe Electro-Magnetic Lock
_____ 1" _____ 1"		_____ Surface applied push bar exit hardware
Finish:		_____ Recessed push bar exit hardware
_____ Clear (204) _____ Dk bronze (313)		_____ Paddle exit hardware (Fixed Sidelite)
_____ Special anodize _____ Paint/Clad		_____ Key Switches in lieu of Rocker Switch
_____ Prep for paint by distributor		_____ Additional Holding Beams Qty _____
Threshold:		_____ Access cover on opposite side of header
_____ 1/2" Standard _____ 1/4" Optional		_____ Rain Cover for Acusensor M
_____ Through Door Opening		_____ Alarm Contact
_____ Under Jamb* _____		_____ Prep as Clean Room unit
		_____ Change Rocker Switches location (include diagram)
* Does the Total Frame Height entered in Frame Size category above include height of threshold?		_____ Aluminum Cart Bars (specify panels need bars)
_____ Yes < or > _____ No		_____ Additional sidelite(s)
_____ Between Jamb _____ Other		Bottom Rail:
		_____ Width _____
		_____ Standard _____ 10" _____ Other _____ Height _____ Muntins _____

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form. Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. The hook on the cover is ripped off on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on.