

NABCO Entrances - Telescopic Slide Door - ORDER FORM

Quote:		Page:		USA	Revision
Company:		Distributor #:		2022	2.8.T
Date:		Job Name:		of	
PO #:		Contact:		Door #:	
Drop Ship to:					
Ship Method:				Date to Ship:	

Notes:

Type of Unit:	GT1175 -drawing #	Jamb Tubes:	None Required
Quantity		N/A	Standard ~ 1-3/4" x 4-1/2"
Bi-part	Fixed Sidelite	N/A	1-3/4" x 4-1/2" Single Pocket
Single	Full Open	N/A	1-3/4" x 4-1/2" Double Pocket
	N/A	N/A	1-3/4" x 4-1/2" Without Pockets
Telescopic		N/A	1-3/4" x 6-3/8"
All-Glass (FSL Only)		N/A	2" x 5"
Surface applied (* see note 1)			2" x 7"
		N/A	4-1/2" x 4-1/2" Jamb Tubes (see below)
Custom Surface Applied Units:			except AG or Telescopic
Surface Applied to Exterior with Wall Track		Muntin Bars:	
Surface Applied to Interior, Breakout Thru Opening		2" std.	4"
(Wall Opening required to size doors correctly)		8"	6-3/8"
x	Wall Opening (W x H)	No muntins required	
Hand of Unit:		Special	
Right hand	viewed from	Standard Height 42-1/4" F.F. - top	
Left hand	panic breakaway side	Special location - F.F. - top	
Frame Size:		Additional Muntin - F.F. - top	
Width	Header Height (std. = 91-1/2")	6-3/8" Muntin Std. - Recessed Panic	
Total Frame Height Including Transom		Additions/Changes:	
Number of Verticals in Transom		Acuzone (in lieu of Acusensor M)	
Clear Door Opening Width		Optex i-One (in lieu of Acusensor M)	
Door/Panel Glass Thickness	Transom Glass Thickness	BEA IXIO-DT1 (in lieu of Acusensor M)	
1/4" (std.)	1/4" (std.)	Angled spacer for Acusensor M	
1/2"	1/2"	Medium Stile (4")	
9/16"	9/16"	Fail Safe Electric Lock	
5/8"	5/8"	Fail Secure Electric Lock	
3/4"	3/4"	N/A	Fail Safe Electro-Magnetic Lock
7/8"	7/8"		Surface applied push bar exit hardware
1"	1"		Recessed push bar exit hardware
Finish:			Paddle exit hardware (Fixed Sidelite)
Clear (204)	Black		Key Switches in lieu of Rocker Switch
Dark bronze (313)	Paint/Clad		Additional Holding Beams Qty _____
Prep for paint by distributor	Special anodized	N/A	Access cover on opposite side of header
Threshold: (* see note 2)		N/A	Rail Locks for All Glass Sliders
1/2" Standard	1/4" Optional	N/A	Include Weathering for All Glass
Through Door Opening		N/A	Prep as Clean Room unit
Under Jamb's *			Change Rocker Switches location (include diagram)
* Does the Total Frame Height entered in Frame Size category above include height of threshold?			Aluminum Cart Bars (specify panels need bars)
Yes < or >	No		Additional sidelite(s)
Between Jamb's	Other		Width
Bottom Rail:			Height
Standard	10"	Other	Muntins

Note 1:

Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. We rip the hook off the cover on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on. If you would like to change the location of the control switches, indicate the desired location in the Notes section above.

Note 2:

On Telescopic doors, a threshold jamb to jamb is necessary on a full open unit. Any threshold option is available for fixed units.