

NABCO- STORM Series Hurricane Doors - Quote Request Form

USA Revision
2022 2.8.T

Quote: _____ Page: _____ of _____
 Company: _____ Distributor #: _____ Door #: _____
 Date: _____ Job Name: _____
 PO #: _____ Contact: _____
 Drop Ship to: _____
 Ship Method: _____ Date to Ship: _____

Notes:

Level E
 H105
 H60

Impact
 Non-Impact

Type of Unit:

Quantity Fixed Sidelite
 Bi-part Full Open
 Single

Muntin Bars:

4" (H105 only)

Hand of Unit:

Right hand *viewed from exterior*
 Left hand *panic breakaway direction*

Bottom Rail:

4" H60
 6.5"
 10"

6.5" H105
 10"

Frame Size:

Width ((H60 max. 16' / H105 max. 18'))
 Header Height less transom (see below)
 H60 max. 7' 7-1/2" H105 max. 8' 8"
 Clear Door Opening Width

Note:
 All hurricane units are equipped with 1/2" jamb to jamb thresholds.

Additions/Changes:

Acuzone (in lieu of Acusensor)
 Optex i-One (in lieu of Acusensor)
 BEA IXIO-DT1 (in lieu of Acusensor)
 Acusensor spacer Part # V-00742
 Medium Stile on H60
 Fail Safe Electric Lock
 Fail Secure Electric Lock
 Adams Rite G86 Panic Bar (H105 only)
 Key Switches in lieu of Rocker Switch
 Additional Holding Beams
 Qty
 Rocker switches at location OTHER than
 on interior jamb face
 (include diagram with order)
 Aluminum Cart Bar P/N 14-11035
 Key Cylinder operated flush bolts
 (H60 only)
 4550 Dead Bolt Lever/s

Finish:

Clear (204) Black
 Dark bronze (313) Paint/Clad
 Prep for paint by distributor Special anodized

Door/Panel Glass Thickness

1/2" Impact H60
 5/16" Non-Impact

7/16" Impact H105
 1/4" Non-Impact

9/16" Impact Level E
 Non-Impact