

# NABCO Entrances - Single Slide Door - Quote Request Form

USA	Revision
2022	2.8.T

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

<b>Type of Unit:</b>	GT1175 -drawing #		Quantity		
NA Bi-part		Fixed Sidelite	<b>Jamb Tubes:</b>	None Required	
Single		Full Open		Standard - 1-3/4" x 4-1/2"	
		Pocketed		1-3/4" x 4-1/2" Single Pocket	
NA Telescopic				1-3/4" x 4-1/2" Double Pocket	
NA All-Glass (FSL Only)	<input type="checkbox"/> to interior <input type="checkbox"/> to exterior <input type="checkbox"/> w/ sidelite <input type="checkbox"/> no sidelite			1-3/4" x 4-1/2" Without Pockets	
Surface applied <sup>*Note 1</sup>				1-3/4" x 6-3/8"	
					2" x 5"
					2" x 7"
<b>Custom Surface Applied Units:</b>				4-1/2" x 4-1/2" Jamb Tubes (see below)	
		Surface Applied to Exterior with Wall Track	<b>Muntin Bars:</b>		
		Surface Applied to Interior, Breakout Thru Opening		2" std. 4"	
		(Wall Opening required to size doors correctly)		8" 6-3/8"	
		x Wall Opening (W x H)		No muntins required	
<b>Hand of Unit:</b> (viewed from panic breakaway side)				Special	
Right hand		Left hand		Standard Height 42-1/4" F.F. - top	
				Special location - F.F. - top	
<b>Frame Size:</b>				Additional Muntin - F.F. - top	
Width		Header Height		6-3/8" Muntin Std. - Recessed Panic	
Total Frame Height Including Transom <sup>*</sup> (std.=91-1/2")			<b>Additions/Changes:</b>		
Number of Verticals in Transom				Acuzone (in lieu of Acusensor M)	
Clear Door Opening Width				Optex i-One (in lieu of Acusensor M)	
<b>Door/Panel Glass Thickness</b>	<b>Transom Glass Thickness</b>			BEA IXIO-DT1 (in lieu of Acusensor M)	
1/4" (std.)	1/4" (std.)			Angled spacer for Acusensor M	
1/2"	1/2"			Medium Stile (4")	
9/16"	9/16"			Fail Safe Electric Lock	
5/8"	5/8"			Fail Secure Electric Lock	
3/4"	3/4"			Fail Safe Electro-Magnetic Lock	
7/8"	7/8"			Surface applied push bar exit hardware	
1"	1"			Recessed push bar exit hardware	
<b>Finish:</b>				Paddle exit hardware (Fixed Sidelite)	
Clear (204)		Dk bronze (313)		Key Switches in lieu of Rocker Switch	
Special anodize		Paint/Clad		Additional Holding Beams Qty _____	
Prep for paint by distributor				Access cover on opposite side of header	
<b>Threshold:</b>				Rain Cover for Acusensor M	
1/2" Standard		1/4" Optional		Alarm Contact	
Through Door Opening				Prep as Clean Room unit	
Under Jamb <sup>*</sup>				Change Rocker Switches location (include diagram)	
				Aluminum Cart Bars (specify panels need bars)	
<b>Bottom Rail:</b>				Additional sidelite(s)	
Standard		10"		Width	
		Other		Height	
				Muntins	

\* Does the Total Frame Height entered in Frame Size category above include height of threshold?

	Yes < or >	No
	Between Jamb	Other

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form. Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. The hook on the cover is ripped off on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on.