

# NABCO - GT1400 Folding Door - Shop Drawing Request FORM

USA	Revision
2022	2.6.T

Quote: \_\_\_\_\_ Page: \_\_\_\_\_ of \_\_\_\_\_  
 Company: \_\_\_\_\_ Distributor #: \_\_\_\_\_ Door #: \_\_\_\_\_  
 Date: \_\_\_\_\_ Job Name: \_\_\_\_\_  
 PO #: \_\_\_\_\_ Contact: \_\_\_\_\_  
 Drop Ship to: \_\_\_\_\_  
 Ship Method: \_\_\_\_\_ Date to Ship: \_\_\_\_\_

Notes: \_\_\_\_\_

**Type of Unit:**

Quantity	
Single Fold	<i>GT1400 folds and breaks</i>
Bi-Fold	<i>open in the same direction</i>

**Hand of Unit:**

Right hand (door slides to the right when viewed from <b>interior</b> )
Left hand (door slides to the <i>left</i> when viewed from <b>interior</b> )

**Frame Size:**

Width			
Header Height (std. = 91-1/2")	<u>Frame Width</u>	<u>Min</u>	<u>Max</u>
Height Including Transom	Bi-Fold	6' 4"	9' 0"
Number of Verticals in Transom	Single Fold	3' 10"	5' 3"
Clear Door Opening Width			

**Door/Panel Glass Thickness**

1/4" (std.)
1/2"
9/16"
5/8"
3/4"
7/8"
1"
Hurricane

**Transom Glass Thickness**

1/4" (std.)
1/2"
9/16"
5/8"
3/4"
7/8"
1"

**Finish:**

Dk bronze (313)	Clear (204)
Prep for paint by distributor	Black
Special anodize	
Paint/Clad	

**Guide Rails:**

(Qty.) Fold Side (matches finish of door)
Length: _____ One Way Traffic (per ANSI 156.10)
Length: _____ Two Way Traffic (per ANSI 156.10)
Length: _____ Other (as specified)

**GT1400 - \_\_\_\_\_ drawing #:**

**Jamb Tubes:**

Standard
1-3/4" x 6-3/8"
2" x 7"
No Jambes Required

**Muntin Bars:**

2" std.
4"
4-1/2"
6-3/8"
No muntins required
Special _____
Standard Height 42-7/8" F.F. - top
Special location - F.F. - top
Additional Muntin - F.F. - top

**Bottom Rail:**

Standard
10"
Other _____

**Additional Sensors:**

Header Mounted Sensors:

(Qty.) Acusensor M
(Qty.) Optex i-One
(Qty.) Optex Reaction2

**Locks:**

Manual - manual lock(s) with thumb turn and key cylinder (standard)
Flush Bolt - lock(s) at fold point(s)
No Cylinder or Flush Bolts
Electro-Magnetic Lock (fail-safe)

**Extras:**

Threshold
Rocker switches at location OTHER than on interior jamb face (include diagram with order)

Refer to Product Configuration and Pricing Manual for Additional Information