

NABCO GT2300 Manual/ICU Swing Door - Shop Drawing Request FORM

USA	Revision
2022	2.6.T

Quote: _____	Page: _____	of _____
Company: _____	Distributor #: _____	Door #: _____
Date: _____	Job Name: _____	
PO #: _____	Contact: _____	
Drop Ship to: _____		
Ship Method: _____	Date to Ship: _____	

Notes: _____

Type of Unit: _____ Quantity _____

Model Type "A" or "B" as viewed from swing side:

_____ "A" Inactive Door - Active Door
 _____ "B" Active Door - Inactive Door

Frame Size:

_____ Width (Frame & Doors) (99-1/2" Maximum)
 _____ Header Height (Standard 87-5/8", Maximum 125")
 _____ Active door width (panel equipped with Latch Handle)
 _____ Inactive door width (panel equipped with Flush Bolt)

Door/Panel Glass Thickness

_____ 1/4" (std.)
 _____ 1" or other

Finish:

_____ Clear (204)
 _____ Dk bronze (313)
 _____ Special anodize
 _____ Paint/Clad
 _____ Prep for paint by distributor

Threshold:

_____ No Threshold (Std)	_____ Under Jambs
_____ Between Jambs	_____ (Included in Height)
	_____ Other

Bottom Rail:

_____ 4" (Standard)
 _____ 5"
 _____ 6-1/2"
 _____ 10"


Top Rail:

_____ 4" (Standard)
 _____ 5"
 _____ 6-1/2"
 _____ 10"

Note: Door gap at bottom is 1/2" standard

Jamb Tubes:

_____ Standard (1-3/4" x 4-1/2" - No Pockets)
 _____ 1-3/4" x 6-3/8"
 _____ 2" x 5"
 _____ 2" x 7"
 _____ No Jambs Required
 _____ Header Width for No Jambs



Hinges are on outside edges of jamb tubes

Muntin Bars:

_____ 2" std.
 _____ 4"
 _____ 6-3/8"
 _____ 8"
 _____ No muntins required

Muntin Height:

_____ Standard Height 42-1/4" F.F. - Top
 _____ Special location - F.F. - Top
 _____ Additional Muntin - F.F. - Top

Options:

_____ Medium Stile
 _____ Smoke Rated Required
 Some Options Affect Smoke Rating

Composite Panels

Check One	_____ All Lites
	_____ Bottom Lites
	_____ Top Lites
Choose Color	_____ Metallic Silver
	_____ Bone White
	_____ Glossy White
Choose Finish	_____ Dark Bronze
	_____ Textured
	_____ Smooth