NABCO ICI	U Automatic/Manual Door -	- <u>ORDER FORM</u>	<u>^</u>	USA Revisio	
				2022 2.6.T	
Quote:			Page:	of	
Company:			Distributor #:	Door #:	
Date:		Job Name	e:		
PO #:		Contac	t:		
Drop Ship to:					
Ship Method:	:		Date to Ship:		
Notes:					
F		lamb Tubasa			
Type of Unit:	Quantity	Jamb Tubes:	3/4" x 4-1/2" (manual only)		
	Quantity		1-3/4" x 4-1/2" (Standard for	Automatic	
Model:			1-3/4" x 4-1/2" (Pocketed)	Automatic)	
woder.	PH Manual (2400M PH)		1-3/4 x 4-1/2 (Pocketed)		
	RH Manual (2400M-RH) LH Manual (2400M-LH)	Bottom Rail:			
	BP Manual (2400M-BP)	bottom Kan.	4" (standard)		
	RH Automatic (2400A-RH)		6-1/2"		
	LH Automatic (2400A-KH)		10"		
	- LIT Automatic (2400A LIT)				
Frame Size:		Muntin Bars:			
Turre 512c.	Width (Max Single: 108"; Max BP 192")	marrent bars,	None		
	Header Height (88" Standard)		2" (std.)		
	(Max: 102")		4"		
Finish:	` '		Muntin Height (42-1/4 std.)		
	Clear (204) (Standard)		_		
	Dark Bronze (313)	Options:			
	Black		Double "D" Handles		
	Paint		Recessed Handles		
	Powder Coat		Positive Latch - Handles Dowr	า	
	Special Anodize		Positive Latch - Recessed Han	idles	
			Medium Stiles (Manual only)	only)	
Door/Panel Glass Thickness			Brush Weathering		
	1/4" (std.)		Vinyl Weathering, No Sweeps		
	1"		UL1784 Smoke Package*		
	Other		MS Lock		
	_		Prep for Electrified Glass (Cor	ntact Engineering Dept)	
Photoeyes: (Optional) None (Standard)			*Requires: Positive Latch		
		Control Switch: (on/off/hold open)			
	Single		Rocker		
	Height #1		Keyed		
	Dual				
	Height #2	Activation:			
			Button		
			Hand-free		
		(Contact Custom	ner Service for Options)		