

NABCO Complete Swing Door System - ORDER FORM

USA Revision
2022 2.8.T

Quote: _____	Page: _____	of _____
Company: _____	Distributor #: _____	Door #: _____
Date: _____	Job Name: _____	
PO #: _____	Contact: _____	
Drop Ship to: _____		
Ship Method: _____	Date to Ship: _____	

Notes: _____

Bottom Load	Side Load
_____ 400 C *	_____ 8400 C *
_____ 400 F *	_____ 8400 F *
_____ Electrical Access Hole in End Cap?	
_____ Electrical Access Hole in Top of Header?	
_____ No Holes Required	
"F" = with center pivot and fingerguard	
"C" = with Continuous Hinge	

2. Swing & Handing:

_____ Inswing (with panic breakout)

_____ Inswing (without panic breakout)

_____ Outswing

(Place Back to Pivot Jamb) RT Hand OUT

_____ RT Hand IN _____ LT Hand OUT

_____ LT Hand IN _____

3. Glass Thickness:

_____ Door Glass Thickness (1/4", 1", other)

_____ Transom Glass Thickness (1/4", 1", other)

(glass not included)

4. Frame Dimensions (to top):

_____ Header Height (90" standard for bottom load)

(91" standard for side load)

_____ Height Including Transom

_____ Threshold (5-1/2" standard width)

_____ Frame Width

5. Pivot type:

_____ Ctr Pivot

_____ Continuous Hinge

6. CU Inswing Tracks:

_____ 12" Track - A-60639 (204), A-70639 (313)

_____ 21" Track - A-00481 (204), A-70481 (313)

7. Jamb Tubes

_____ 1-3/4" x 4-1/2" (standard)

_____ 4-1/2" x 4-1/2" jambs (204 or 313 finish)

_____ Existing (specify width and height)

8. Door Pivot Location:

_____ Outer Jambs _____ Center Post (send sketch)

9. Application:

_____ Single _____ Simultaneous Pair

10. Finish:

_____ Clear (204) _____ Dark bronze (313)

11. Adds:

_____ 10" Bottom rail

_____ Acusensor M on swing side

_____ Additional aluminum cart bars (ea)

_____ Transom (up to 120")

_____ Vertical in transom

12. Changes & Deducts:

_____ Deduct Guide rails

_____ Acusensor in lieu of Optex Reaction Two

_____ Deduct one Aluminum Cart Bar

_____ Deduct Finger Guards

_____ Deduct Jamb Tubes

_____ Deduct Muntin

_____ Deduct MS Lock (standard)

_____ Deduct Push Bar and Handle

_____ Key switch in lieu of rocker switch

_____ Deduct Sensing System

13. Profile:

_____ Narrow Stile (standard profile)

_____ Medium Stile

14. Swing Door Size:

_____ Width _____ Narrow Stile (2-1/8")

_____ Height _____ Medium Stile (4")

_____ Muntin Bar Height (standard 42-1/4" to top)

_____ Muntin Size _____ 2" Standard

_____ Other Size (Special)

15. Door Panel Accessories:

_____ Push Bar Both Sides

(in lieu of standard Push Bar & Pull Handle)

_____ Prep in Field (hardware shipped loose)

_____ Extra sidelite/s (include drawing with order)

Frame Dimensions (in Inches)

Header Height

0

Enter Frame Width

0

Frame Height

0

Muntin Bar Height

0

Door Height

0

Door Width

0

1" Finger Guard

