


NABCO- GT20 Swing Door Operator Quote Request Form

USA	Revision
2022	2.8.N

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

Include decal packet for: <input type="checkbox"/> Full Auto <input type="checkbox"/> Low Energy Type of Header: <input type="checkbox"/> Low Profile CU, Single, Pt # GT20-0100 <input type="checkbox"/> Low Profile CU, Sim Pair, Pt # GT20-0101 Header heights: <input type="checkbox"/> Low Profile = 3-3/4" Arms and Tracks <input type="checkbox"/> Outswing Arm & Shoe <input type="checkbox"/> Inswing Arm and Track <input type="checkbox"/> Reveal (back of operator to face of door) Arm and Track can be used as follows: <i>Interior door: <u>outswing or inswing</u></i> <i>Exterior door: <u>inswing only</u></i> <input type="checkbox"/> M-01791 Inswing Arm Must be used on Inswing Units with Reveals between 0" - 5" Alternate spindle extensions: <input type="checkbox"/> Pt # V-00513 Length: 1.4" (36mm) <input type="checkbox"/> Pt # V-00407 Length: 2.2" (56mm) <input type="checkbox"/> Pt # V-00408 Length: 3.4" (86mm)	Architectural Binder Dwg # <input type="text"/> Quantity <input type="text"/> Door Pivot: <input type="checkbox"/> Butt & Hinge <input type="checkbox"/> Center Pivot <input type="checkbox"/> Jamb Size 1-3/4" <input type="checkbox"/> Other Finish: <input type="checkbox"/> Clear (204) <input type="checkbox"/> Black <input type="checkbox"/> Dark bronze (313) <input type="checkbox"/> Paint/Clad <input type="checkbox"/> Prep for paint by distributor <input type="checkbox"/> Special anodized Additional Sensors: <input type="checkbox"/> Acusensor M Presence Sensor Pt # A-01306 <input type="checkbox"/> Reaction Two Pt # V-00173 <input type="checkbox"/> OA Edge1 Sensor, w/One Module Pt # V-00224 <input type="checkbox"/> OA Edge2 Sensor, w/Two Modules Pt # V-00163 <input type="checkbox"/> Wireless Switch Kit, SS with Etched and Paint Filled Legends Plug in Relay Board: <input type="checkbox"/> Provides 4 independent relay outputs Pt # V-00326 Mode Selector Switch <input type="checkbox"/> Change from header mounted mode switch to jamb mounted (applies to conversion unit only) Total Header Length <input type="text"/> inches (= Door Opening Width + 1.75" overlap each side)
--	---



Optional Swing Door Leaf and Frame:

Door Panel Accessories: <input type="checkbox"/> Push Bar & Pull Handle (standard) <input type="checkbox"/> Push Bar Both Sides <input type="checkbox"/> Panic Hardware <input type="checkbox"/> No muntins required <input type="checkbox"/> Glass Thickness (1/4", 1", other)	Swing Door Size: <input type="text"/> Width <input type="text"/> Narrow Stile (2-1/8") <input type="text"/> Height <input type="text"/> Medium Stile (4") <input type="checkbox"/> Muntin Bar (optional) <input type="text"/> 2" <input type="text"/> 4" <input type="text"/> Special <input type="text"/>
Frame: <input type="text"/> Header Height (91" Side Load) <input type="text"/> Height Including Transom <input type="text"/> Threshold <input type="text"/> Width	

*** Raising the arm could prevent it from clearing frame mounted door stops located on the underside of the frame