

NABCO Entrances - GT500 Swing Door Operator- Quote Request FORM

USA
2022

Revision
2.8.T

Quote:

Company:

Date:

PO #:

Drop Ship to:

Ship Method:

Page:

Distributor #:

Job Name:

Contact:

of

Door #:

Notes:

Type of Header:

8350

350

8500 *

500

Architectural Binder Dwg #

Door Pivot Location:

Outer Jamb Tubes

Jamb Size 1-3/4"

Finish:

Clear (204)

Dark bronze (313)

Prep for paint by distributor

Quantity

Center Post

Other

Black

Paint/Clad

Special anodized

Access Holes - except Overhead Concealed

Electrical Access Hole in End Cap

Electrical Access Hole in Top of Header

No Holes Required

Send Sketch for Center Post Application

Application:

Single

Dbl. Egress

Simultaneous Pair

Dual

OPMAN

Hand of Unit:

(Place Back to Pivot Jamb)

OPERATOR

MANUAL CLOSER

Rt Hand

Rt Hand

Lt Hand

Lt Hand

CU Inswing Tracks:

12" Track - A-60639 (204), A-70639 (313)

21" Track - A-00481 (204), A-70481 (313)

Direction of Door Swing:

(Qty.) Inswing

(Qty.) Outswing

(Qty.) Inswing with Panic

Pivot type:

Ctr Pivot

with FG

no FG

Swing Clear

Butt Hinge/Offset Pivot

Reveal:

Outswing

Inswing

Webb Depth of Door Panel:

5/8"

1-9/16"

7/8"

Other web depths

1"

Specify depth

Sideload Mounting Brackets:

Full Length Sideload Mounting Bracket Kit

Two Piece Sideload Mounting Bracket Kit

Rivnut Kit, CU, Bottom Load P/N M-01420

Rivnut Kit, Sideload and GT710 P/N A-01197

Rivnut Kit, OHC, Bottom Load P/N A-00642

Optional Swing Door Leaf and Frame:

Swing Door Size:

Width

Narrow Stile (2-1/8")

Height

Medium Stile (4")

Muntin Bar (optional)

2"

4"

Special

No muntins required

Glass Thickness (1/4", 1", other)

Frame:

Header Height (90" Bottom Load - 91" Side Load)

Height Including Transom

Threshold

Width

Door Panel Accessories:

Push Bar & Pull Handle (standard)

Push Bar Both Sides

Panic Hardware

Include Finger Guard

Sizing:

Door Width

Header Length