

NABCO ICU TELESCOPIC

AUTOMATIC & MANUAL ICU SLIDING DOORS



Whisper-quiet Performance, In Sizes and Configurations to Exceed Expectations

- 56 1/2" clear door opening width for easier access (at a 96" typical frame width)
- Flush bolt-free system not requiring additional steps to breakout
- Maintenance friendly design resolving issues against improper installations
- Smoke rated package to meet UL1784 & NFPA 105 requirements
- Extra duty anodized roller track for long lasting durability
- Electrified Glass Option Available for increased privacy

Great in the Following Applications:

- | | |
|-----------------------|-----------------------|
| • Hospitals | • Birth Centers |
| • Urgent Care Centers | • Hospital Rooms |
| • Emergency Medicine | • Critical Care Units |
| • Clinics | |

NABCO ICU TELESCOPIC

AUTOMATIC & MANUAL ICU SLIDING DOORS

The Standard Quiet, High-Performance Entrance Solution

The NABCO ICU Manual and Automatic Telescopic Sliding Doors provides the widest room access available with a 46 ½" clear door opening (at a 96" typical frame width) in a full-open breakout, and trackless-style unit. The flush-bolt free system in NABCO's new Automatic and Manual ICU sliding doors are ideally suited for intensive care and cardiac-care units where large access areas are required for trouble-free transport of beds, gurneys and other medical equipment and airborne germs must be kept from spreading to other areas.



NABCO ICU Manual Telescopic (2400MT) with Electrified Privacy Glass



Wide Clear Door Opening

Now Available with Electrified Glass Panels!

Product Information

Configuration	3 Panels; Trackless
Header Dimensions	10 ½" [270] x 5" [127]
Package Width	84" [2134] - 144" [3658]
Standard Finishes	Clear Anodized
Optional Finishes	Dark Bronze, Black Anodized Painted, Clad, or Special Anodized
Configurations	Single
Standard Features	4" Bottom Rails, 2" Muntins (42 ¼" From Finished Floor), 2 ½" Narrow Stiles, 1¾" x 6¾" Jamb, Vinyl Weathering, Header Mounted Sensors, ON/OFF/Hold Open Rocker Switch, ½" Tall Glass Stops for ¼" Glass
Available Options	UL1784 & NFPA 105 Smoke Package, Positive Latch, 6 ½" or 10" Bottom Rails, Other Handles, 4" Muntins, Photo-eyes, Alternative Glass Sizes up to 1" Thick, Electrified Privacy Glass, Custom Finishes
Code Compliance	ANSI A156.10
Approvals	UL, ULC

Trackless, 1-Step Break-out

Wide frame sizes, for wide door opening and full-breakout for moving patients and equipment.

Smoke Infiltration Rated

UL1784 is the Standard for Air Leakage tests of Door Assemblies and Other Opening Protectives. Order the smoke package to limit air infiltration.

Selection Guide

FRAME WIDTH	DOOR OPENING	FULL BREAKOUT OPENING	LEAD DOOR	TRAIL DOOR	SIDELITE
84" [2134]	48 ½" [1232]	73 ¾" [1870]	31" [787]	24 ½" [622]	29 ¾" [741]
96" [2438]	56 ½" [1435]	85 ¾" [2175]	35" [889]	28 ½" [724]	33 ¾" [843]
108" [2743]	64 ½" [1638]	97 ¾" [2480]	39" [991]	32 ½" [826]	37 ¾" [945]
120" [3048]	72 ½" [1842]	109 ¾" [2784]	43" [1092]	36 ½" [927]	41 ¾" [1046]
144" [3658]	88 ½" [2248]	133 ¾" [3394]	51" [1295]	44 ½" [1130]	49 ¾" [1249]



Design your new facility
with NABCO Entrances:

Visit: [NABCOentrances.com/
product/nabco-icu-
automatic-telescopic-
sliding-door/](https://www.nabcoentrances.com/product/nabco-icu-automatic-telescopic-sliding-door/)



Member of the Nabtesco Group



NABCO Entrances Inc.
582 W18717 Gemini Drive
Muskego, WI 53150
[NABCOentrances.com](https://www.nabcoentrances.com)
info@NABCOentrances.com
P 877-622-2694

US-E-V.05.20.2025