# NABCO Entrances - GT1175 Bi-part Slide Door - ORDER FORM

$=USA Dollar 2024 | Revision 1.6.T

Quote: | Page: | of
Company: | Distributor #: | Door #:
Date: | Job Name:
PO #: | Contact:
Drop Ship to:
Ship Method: | Date to Ship:

Notes:

**Type of Unit:**
- X Bi-part
- Surface applied *Note 1
  - to interior
  - to exterior
  - w/ sidelite
  - no sidelite (P-panel with Wall Track)
- Fixed Sidelite
- Full Open
- Pocketed

**Custom Surface Applied Units:**
- SA to Exterior with Wall Track
- SA, Breakout Thru Opening

**Frame Size:**
- Width (in)
- Header Height (in)
- Clear Door Opening Width (in)

**Wall Opening** (required to size doors correctly for SA Units)
- x
- Wall Opening (W x H)

**Transom:** YES <or> NO
- Total Frame Height Including Transom (std.=91-1/2")
- Number of Verticals in Transom

**Door/Panel Glass Thickness**
- 1/4" (std.)
- Other

**Transom Glass Thickness**
- 1/4" (std.)
- Other

Other Glass Thickness Options: 1/2", 9/16", 5/8", 3/4", 7/8", 1"

**Finish:**
- Clear (204)
- Special anodize
- Powder Coat
- Prep for paint by distributor
- Dark bronze (313)
- Black
- Paint
- Color

**Threshold:**
- NONE (Fixed Sidelite ONLY)
- 1/2" Standard Between Jambs
- 1/4" Through Door Opening
- 1/4" Between Jambs (Fixed Sidelite ONLY)
- 1/2" Under Sidelite Only (FO Standard)
- 1/2" Under Jambs*

*Does the Total Frame Height entered in Frame Size include height of threshold?

YES <or> NO

**Bottom Rail:**
- Standard
- 10"
- 6-1/2"
- Other

**Quantity** | **Drawing #**

**Additions/Changes:**

| | | |
|---|---|---|
| *Panic Device:* | | Surface applied push bar exit hardware |
| | | Recessed push bar exit hardware |
| | | Paddle exit hardware (Fixed Sidelite) |
| *Electric Lock:* | | Fail Safe Electric Lock |
| | | Fail Secure Electric Lock |
| | | Fail Safe Electro-Magnetic Lock |
| *Armored Strike:* | | Armored Strike |
| *Door Closer:* | | # of Door Closer(s) instead of Limit Arm |
| *Ex.Holding Beam:* | | # of Additional Holding Beams (1 Beam Standard) |
| *Tie Rods:* | | Tie Rods Required (Y/N) |
| *Clean Room:* | | Prep as Clean Room unit |
| *Nose Caster:* | | Req. for panels over 200 lbs. or wider than 42" |
| *Sensors:* | | Sidelite Protection |
| | | Angled spacer for Acusensor M |
| | | Rain Cover for Acusensor M |
| *Upgrade Sensor:* | | Conceal, Acuzone, i-One, or ULTIMO |
| *Alarm Contact:* | | Select Yes or No Alarm/Security Contact |
| *Cart Bars:* | | Aluminum Cart Bars (specify panels for Bars) |
| *Muntin Bars:* | | 2" (Standard) |
| | | Other: 4", 8", 6-3/8" (Standard Recessed Panic) |
| | | None |
| | | Standard Height 42-1/4" F.F. - top |
| | | Special location - F.F. - top |
| | | Additional Muntin - F.F. - top |
| *Medium Stiles* | | Change to Medium Stile (4") |
| *Switches* | | Key Switches in lieu of Rocker Switch |
| | | Change Rocker Switches location (include diagram) |
| *Exit Indicator* | | Exit Indicator |
| *Reverse Access* | | Access cover on opposite side of header |
| *Add. Sidelite(s)* | | # of Additional sidelite(s) |
| | | Width (in) |
| | | Height (in) Muntins |

**Jamb Tubes:**
- None Required
- 1-3/4" x 4-1/2" (Standard)
- or
  - 1-3/4" x 4-1/2" Single Pocket
  - 1-3/4" x 4-1/2" Double Pocket
  - 1-3/4" x 4-1/2" Without Pockets
- 1-3/4" x 6-3/8"
- 2" x 7"
- 2" x 5"
- 4-1/2" x 4-1/2"

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form. Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. The hook on the cover is ripped off on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on.