

Quote:

Company:

Date:

PO #:

Drop Ship to:

Ship Method:

Page:

Distributor #:

Job Name:

Contact:

Date to Ship:

of

Door #:

Notes:

Type of Unit:

Bi-part

Fixed Sidelite

Surface applied^{*Note 1}

Full Open

to interior

Pocketed

to exterior

w/ sidelite

no sidelite (P-panel with Wall Track)

Custom Surface Applied Units:

SA to Exterior with Wall Track

SA, Breakout Thru Opening

Quantity

Drawing #

Additions/Changes:

Panic Device:

Surface applied push bar exit hardware

Recessed push bar exit hardware

Paddle exit hardware (Fixed Sidelite)

Electric Lock:

Fail Safe Electric Lock

Fail Secure Electric Lock

Fail Safe Electro-Magnetic Lock

Armored Strike:

Armored Strike

Door Closer:

of Door Closer(s) instead of Limit Arm

Ex.Holding Beam:

of Additional Holding Beams (1 Beam Standard)

Tie Rods:

Tie Rods Required (Y/N)

Clean Room:

Prep as Clean Room unit

Nose Caster:

Req. for panels over 200 lbs. or wider than 42"

Sensors:

Sidelite Protection

Angled spacer for Acusensor M

Rain Cover for Acusensor M

Upgrade Sensor:

Conceal, Acuzone, i-One, or ULTIMO

Alarm Contact:

Select Yes or No Alarm/Security Contact

Cart Bars:

Aluminum Cart Bars (specify panels for Bars)

Muntin Bars:

2" (Standard)

Other: 4", 8", 6-3/8" (Standard Recessed Panic)

None

Standard Height 42-1/4" F.F. - top

Special location - F.F. - top

Additional Muntin - F.F. - top

Medium Stiles

Change to Medium Stile (4")

Switches

Key Switches in lieu of Rocker Switch

Change Rocker Switches location (include diagram)

Exit Indicator

Exit Indicator

Reverse Access

Access cover on opposite side of header

Add. Sidelite(s)

of Additional sidelite(s)

Width (in)

Height (in)

Muntins

Jamb Tubes:

1-3/4" x 4-1/2" (Standard)

1-3/4" x 4-1/2" Single Pocket

1-3/4" x 4-1/2" Double Pocket

1-3/4" x 4-1/2" Without Pockets

1-3/4" x 6-3/8"

2" x 7"

2" x 5"

4-1/2" x 4-1/2"

Frame Size:

Width (in)

Header Height (in)

Clear Door Opening Width (in)

Wall Opening (required to size doors correctly for SA Units)

x

Wall Opening (W x H)

Transom:

YES

<or>

NO

Total Frame Height Including Transom (std.=91-1/2")

Number of Verticals in Transom

Door/Panel Glass Thickness

Transom Glass Thickness

1/4" (std.)

1/4" (std.)

Other

Other

Other Glass Thickness Options: 1/2", 9/16", 5/8", 3/4", 7/8", 1"

Finish:

Clear (204)

Dark bronze (313)

Special anodize

Black

Powder Coat

Paint

Prep for paint by distributor

Color

Threshold:

NONE (Fixed Sidelite ONLY)

1/2" Standard Between Jambs

1/4" Through Door Opening

1/4" Between Jambs (Fixed Sidelite ONLY)

1/2" Under Sidelite Only (FO Standard)

1/2" Under Jambs*

*Does the Total Frame Height entered in Frame Size include height of threshold?

YES

<or>

NO

Bottom Rail:

Standard

6-1/2"

10"

Other

Quantity

Drawing #

Additions/Changes:

Panic Device:

Surface applied push bar exit hardware

Recessed push bar exit hardware

Paddle exit hardware (Fixed Sidelite)

Electric Lock:

Fail Safe Electric Lock

Fail Secure Electric Lock

Fail Safe Electro-Magnetic Lock

Armored Strike:

Armored Strike

Door Closer:

of Door Closer(s) instead of Limit Arm

Ex.Holding Beam:

of Additional Holding Beams (1 Beam Standard)

Tie Rods:

Tie Rods Required (Y/N)

Clean Room:

Prep as Clean Room unit

Nose Caster:

Req. for panels over 200 lbs. or wider than 42"

Sensors:

Sidelite Protection

Angled spacer for Acusensor M

Rain Cover for Acusensor M

Upgrade Sensor:

Conceal, Acuzone, i-One, or ULTIMO

Alarm Contact:

Select Yes or No Alarm/Security Contact

Cart Bars:

Aluminum Cart Bars (specify panels for Bars)

Muntin Bars:

2" (Standard)

Other: 4", 8", 6-3/8" (Standard Recessed Panic)

None

Standard Height 42-1/4" F.F. - top

Special location - F.F. - top

Additional Muntin - F.F. - top

Medium Stiles

Change to Medium Stile (4")

Switches

Key Switches in lieu of Rocker Switch

Change Rocker Switches location (include diagram)

Exit Indicator

Exit Indicator

Reverse Access

Access cover on opposite side of header

Add. Sidelite(s)

of Additional sidelite(s)

Width (in)

Height (in)

Muntins

Jamb Tubes:

1-3/4" x 4-1/2" (Standard)

1-3/4" x 4-1/2" Single Pocket

1-3/4" x 4-1/2" Double Pocket

1-3/4" x 4-1/2" Without Pockets

1-3/4" x 6-3/8"

2" x 7"

2" x 5"

4-1/2" x 4-1/2"

Threshold:

NONE (Fixed Sidelite ONLY)

1/2" Standard Between Jambs

1/4" Through Door Opening

1/4" Between Jambs (Fixed Sidelite ONLY)

1/2" Under Sidelite Only (FO Standard)

1/2" Under Jambs*

*Does the Total Frame Height entered in Frame Size include height of threshold?

YES

<or>

NO

Bottom Rail:

Standard

6-1/2"

10"

Other

Quantity

Drawing #

Additions/Changes:

Panic Device:

Surface applied push bar exit hardware

Recessed push bar exit hardware

Paddle exit hardware (Fixed Sidelite)

Electric Lock:

Fail Safe Electric Lock

Fail Secure Electric Lock

Fail Safe Electro-Magnetic Lock

Armored Strike:

Armored Strike

Door Closer:

of Door Closer(s) instead of Limit Arm

Ex.Holding Beam:

of Additional Holding Beams (1 Beam Standard)

Tie Rods:

Tie Rods Required (Y/N)

Clean Room:

Prep as Clean Room unit

Nose Caster:

Req. for panels over 200 lbs. or wider than 42"

Sensors:

Sidelite Protection

Angled spacer for Acusensor M

Rain Cover for Acusensor M

Upgrade Sensor:

Conceal, Acuzone, i-One, or ULTIMO

Alarm Contact:

Select Yes or No Alarm/Security Contact

Cart Bars:

Aluminum Cart Bars (specify panels for Bars)

Muntin Bars:

2" (Standard)

Other: 4", 8", 6-3/8" (Standard Recessed Panic)

None

Standard Height 42-1/4" F.F. - top

Special location - F.F. - top

Additional Muntin - F.F. - top

Medium Stiles

Change to Medium Stile (4")

Switches

Key Switches in lieu of Rocker Switch

Change Rocker Switches location (include diagram)

Exit Indicator

Exit Indicator

Reverse Access

Access cover on opposite side of header

Add. Sidelite(s)

of Additional sidelite(s)

Width (in)

Height (in)

Muntins

Jamb Tubes:

1-3/4" x 4-1/2" (Standard)

1-3/4" x 4-1/2" Single Pocket

1-3/4" x 4-1/2" Double Pocket

1-3/4" x 4-1/2" Without Pockets

1-3/4" x 6-3/8"

2" x 7"

2" x 5"

4-1/2" x 4-1/2"

Threshold:

NONE (Fixed Sidelite ONLY)

1/2" Standard Between Jambs

1/4" Through Door Opening

1/4" Between Jambs (Fixed Sidelite ONLY)

1/2" Under Sidelite Only (FO Standard)

1/2" Under Jambs*

*Does the Total Frame Height entered in Frame Size include height of threshold?

YES

<or>

NO

Bottom Rail:

Standard

6-1/2"

10"

Other

Quantity

Drawing #

Additions/Changes:

Panic Device:

Surface applied push bar exit hardware

Recessed push bar exit hardware

Paddle exit hardware (Fixed Sidelite)

Electric Lock:

Fail Safe Electric Lock

Fail Secure Electric Lock

Fail Safe Electro-Magnetic Lock

Armored Strike:

Armored Strike

Door Closer:

of Door Closer(s) instead of Limit Arm

Ex.Holding Beam:

of Additional Holding Beams (1 Beam Standard)

Tie Rods:

Tie Rods Required (Y/N)

Clean Room:

Prep as Clean Room unit

Nose Caster:

Req. for panels over 200 lbs. or wider than 42"

Sensors:

Sidelite Protection

Angled spacer for Acusensor M

Rain Cover for Acusensor M

Upgrade Sensor:

Conceal, Acuzone, i-One, or ULTIMO

Alarm Contact:

Select Yes or No Alarm/Security Contact

Cart Bars:

Aluminum Cart Bars (specify panels for Bars)

Muntin Bars:

2" (Standard)

Other: 4", 8", 6-3/8" (Standard Recessed Panic)

None

Standard Height 42-1/4" F.F. - top

Special location - F.F. - top

Additional Muntin - F.F. - top

Medium Stiles

Change to Medium Stile (4")

Switches

Key Switches in lieu of Rocker Switch

Change Rocker Switches location (include diagram)

Exit Indicator

Exit Indicator

Reverse Access

Access cover on opposite side of header

Add. Sidelite(s)

of Additional sidelite(s)

Width (in)

Height (in)

Muntins

Jamb Tubes:

1-3/4" x 4-1/2" (Standard)

1-3/4" x 4-1/2" Single Pocket

1-3/4" x 4-1/2" Double Pocket

1-3/4" x 4-1/2" Without Pockets

1-3/4" x 6-3/8"

2" x 7"

2" x 5"

4-1/2" x 4-1/2"

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form. Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. The hook on the cover is ripped off on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on.