

NABCO Entrances - GT1175 Single Slide Door - Drawing Request FORM

\$=USA Dollar Revision
2024 1.6.T

Quote:		Page:		of	
Company:		Distributor #:		Door #:	
Date:		Job Name:			
PO #:		Contact:			
Drop Ship to:					
Ship Method:		Date to Ship:			

Notes:

Type of Unit:		Fixed Sidelite
Single		
Surface applied	*Note 1	Full Open
		Pocketed
to interior		
to exterior	Hand of Unit: (viewed from panic breakaway side)	
w/ sidelite		Right hand
no sidelite		Left hand
(P-panel w/Wall Track)		
Custom Surface Applied Units:		
SA, Breakout Thru Opening		

Frame Size:		
Width (in)		Header Height (in)
Clear Door Opening Width (in)		
Wall Opening (required to size doors correctly for SA Units)		
x		Wall Opening (W x H)
Transom:	YES	<or> NO
Total Frame Height Including Transom (std.=91-1/2")		
Number of Verticals in Transom		

Door/Panel Glass Thickness	Transom Glass Thickness
1/4" (std.)	1/4" (std.)
Other	Other
Other Glass Thickness Options: 1/2", 9/16", 5/8", 3/4", 7/8", 1"	
Finish:	
Clear (204)	Dark bronze (313)
Special anodize	Black
Powder Coat	Paint
Prep for paint by distributor	Color

NONE (Standard)	
1/2" Standard Between Jambs	
1/4" Between Jambs (Fixed Sidelite ONLY)	
1/2" Under Jambs*	
*Does the Total Frame Height entered in Frame Size include height of threshold?	
YES	<or> NO

Bottom Rail:	
Standard	6-1/2"
10"	Other

Note 1: On surface applied units, indicate the desired location of rocker switches in Notes area at top of this form. Since a telescopic unit has covers on both sides of the header, when it is surface applied the access to the interior is limited to one side of the header. The hook on the cover is ripped off on the surface applied side so that the cover can be slid downward for access to the drive belt on that side. There will be screws in the bottom of the cover holding it on.

Quantity		Drawing #
----------	--	-----------

Additions/Changes:	
Panic Device:	Surface applied push bar exit hardware
	Recessed push bar exit hardware
	Paddle exit hardware (Fixed Sidelite)
Electric Lock:	Fail Safe Electric Lock
	Fail Secure Electric Lock
	Fail Safe Electro-Magnetic Lock
Armored Strike:	Armored Strike
Door Closer:	# of Door Closer(s) instead of Limit Arm
Ex.Holding Beam:	# of Additional Holding Beams (1 Beam Standard)
Tie Rods:	Tie Rods Required (Y/N)

Clean Room:	Prep as Clean Room unit
Nose Caster:	Req. for panels over 200 lbs. or wider than 42"
Sensors:	Sidelite Protection
	Angled spacer for Acusensor M
	Rain Cover for Acusensor M
Upgrade Sensor:	Conceal, Acuzone, i-One, or ULTIMO
Alarm Contact:	Select Yes or No Alarm/Security Contact
Cart Bars:	Aluminum Cart Bars (specify panels for Bars)

Muntin Bars:	2" (Standard)
	Other: 4", 8", 6-3/8" (Standard Recessed Panic)
	None
	Standard Height 42-1/4" F.F. - top
	Special location - F.F. - top
	Additional Muntin - F.F. - top

Medium Stiles	Change to Medium Stile (4")
Switches	Key Switches in lieu of Rocker Switch
	Change Rocker Switches location (include diagram)
Exit Indicator	Exit Indicator
Reverse Access	Access cover on opposite side of header

Add. Sidelite(s)	# of Additional sidelite(s)
	Width (in)
	Height (in)
	Muntins

Jamb Tubes:	None Required
1-3/4" x 4-1/2" (Standard)	
or	
1-3/4" x 4-1/2" Single Pocket	
1-3/4" x 4-1/2" Double Pocket	
1-3/4" x 4-1/2" Without Pockets	
1-3/4" x 6-3/8"	2" x 7"
2" x 5"	4-1/2" x 4-1/2"